

DNV Master Link Grade 8 P-6810

Product information



The Green Pin® DNV Master Link is perfect for offshore use. The Master Link is DNV-certified and has a large opening to accommodate larger lifting points and crane hooks. Moreover, the coating of the DNV Master Link ensures long-term durability, even under severe environmental conditions. The DNV Master Link is available in a range with a working load limit from 4.1 up to 100 ton.

... [Read more](#)

Material: Alloy steel, Grade 8

Marking: According to standard

Temperature range: -40°C up to +200°C


Standard: DNV 2.7-1 Approved, EN 1677-4

Safety factor: 5:1

Grade: 8

DNV Master Link Grade 8 P-6810

Blueprint



Technical data

Part code	WLL ton	a mm	b mm mm	c mm	Weight kg
401100410480	4.1	16	150	75	0.68
401100700480	7	22	270	140	2.28
401100930480	9.3	26	270	140	3.11
401101450480	14.5	28	270	140	3.78
401101900480	19	32	270	140	5.02
401101950480	19.5	28	200	110	3
401102600480	26	36	270	140	6.46
401103050480	30.5	40	280	155	8.46
401104000480	40	45	320	175	12.2
401105100480	51	50	350	195	16.5
401107500480	75	65	410	220	33
401110000480	100	75	450	250	49