



GN HK14 Softsling Friendly ROV Hook

Product information

Material: Alloy Steel

Marking: According to standard

Temperature range: -40°C up to +200°C

Standard: EN 10204

Safety factor: 4:1

| Part code | WLL | MBL | A | B, | C | D, | E | F | G, | H, | I mm | K | Weight |
|--------------|-------|-------|-----|-----|-----|-----|-------|-----|-----|-----|---------|-------|--------|
| 420504001260 | 42.5 | 170 | 95 | 110 | 120 | 110 | 339 | 41 | 68 | 55 | 80 | 323 | 44 |
| 420505001260 | 55 | 220 | 103 | 120 | 140 | 125 | 392 | 49 | 73 | 60 | 90 | 366 | 66 |
| 420506301260 | 63 | 252 | 109 | 130 | 160 | 140 | 423 | 53 | 85 | 70 | 100 | 406 | 90 |
| 420508001260 | 85 | 340 | 119 | 140 | 180 | 160 | 465 | 60 | 90 | 80 | 120 | 453 | 133 |
| 420510001260 | 100 | 400 | 142 | 160 | 190 | 165 | 530 | 65 | 110 | 100 | 140 | 495 | 187 |
| 420515001260 | 150 | 600 | 157 | 180 | 230 | 200 | 590 | 70 | 120 | 120 | 180 | 588 | 314 |
| 420520001260 | 200 | 800 | 180 | 210 | 260 | 230 | 678 | 78 | 135 | 145 | 200 | 665 | 467 |
| 420525001260 | 250 | 1,000 | 218 | 250 | 290 | 260 | 750 | 90 | 150 | 170 | 230 | 743 | 656 |
| 420530001260 | 300 | 1,200 | 259 | 300 | 320 | 290 | 865 | 100 | 160 | 180 | 260 | 832 | 915 |
| 420540001260 | 400 | 1,600 | 280 | 320 | 350 | 320 | 910 | 105 | 180 | 200 | 300 | 909 | 1,218 |
| 420550001260 | 500 | 2,000 | 294 | 340 | 390 | 340 | 985 | 110 | 190 | 220 | 320 | 982 | 1,541 |
| 420560001260 | 600 | 2,400 | 304 | 350 | 420 | 370 | 1,035 | 120 | 210 | 250 | 340 | 1,037 | 1,883 |
| 420570001260 | 700 | 2,800 | 317 | 360 | 450 | 390 | 1,060 | 125 | 220 | 280 | 380 | 1,097 | 2,290 |
| 420580001260 | 800 | 3,200 | 327 | 380 | 500 | 440 | 1,180 | 140 | 240 | 300 | 400 | 1,213 | 2,994 |
| 420590001260 | 900 | 3,600 | 338 | 400 | 520 | 460 | 1,260 | 150 | 260 | 320 | 420 | 1,282 | 3,565 |
| 420510001261 | 1,000 | 4,000 | 353 | 420 | 560 | 480 | 1,340 | 160 | 280 | 340 | 440 | 1,345 | 4,250 |
| 420512501261 | 1,250 | 5,000 | 371 | 450 | 600 | 530 | 1,415 | 185 | 310 | 360 | 480 | 1,452 | 5,500 |
| 420515501261 | 1,550 | 6,200 | 394 | 480 | 660 | 590 | 1,505 | 205 | 330 | 360 | 540 | 1,566 | 7,000 |

Blueprint

