Lifting Solutions Group
Axel Johnson International

GN HK14 Softsling Friendly ROV Hook

Product information



The GN HK14 is an ROV hook designed for use with soft slings. Its enlarged radius helps protect the sling from bending damage, which can contribute to a longer service life.

Benefits

- Enlarged radius helps reduce bending damage to the soft sling.
- Helps extend the sling's service life.
- Designed for ROV and offshore lifting operations.

Features

- **Model:** GN HK14
- **Type:** Softsling-friendly ROV hook
- Enlarged contact radius to help protect the sling.

Additional information

- When placing two sling legs in the hook, ensure the angle between them does not exceed 90°.
- The latch does not secure the load if it becomes slack. A positive-locking latch is recommended when slack-load conditions are expected.
- The welded tip of the hook is not a load-bearing part.
- A replacement tip or a hook supplied without a tip is available on request.

Product information is based on the manufacturer's catalogue page. Verify the specifications for the exact configuration before use.

... *Read more*

Material: Alloy Steel
Marking: According to standard
Temperature range: -40°C up to +200°C
Standard: EN 10204

Safety factor: 4:1


Traction Levage
marketingtl@traclev.com

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

GN HK14 Softsling Friendly ROV Hook

Blueprint



Technical data

Part code	WLL ton	MBL ton	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	I mm	K mm	Weight kg
420504001260	42.5	170	95	110	120	110	339	41	68	55	80	323	44
420505001260	55	220	103	120	140	125	392	49	73	60	90	366	66
420506301260	63	252	109	130	160	140	423	53	85	70	100	406	90
420508001260	85	340	119	140	180	160	465	60	90	80	120	453	133
420510001260	100	400	142	160	190	165	530	65	110	100	140	495	187
420515001260	150	600	157	180	230	200	590	70	120	120	180	588	314
420520001260	200	800	180	210	260	230	678	78	135	145	200	665	467
420525001260	250	1,000	218	250	290	260	750	90	150	170	230	743	656
420530001260	300	1,200	259	300	320	290	865	100	160	180	260	832	915
420540001260	400	1,600	280	320	350	320	910	105	180	200	300	909	1,218
420550001260	500	2,000	294	340	390	340	985	110	190	220	320	982	1,541
420560001260	600	2,400	304	350	420	370	1,035	120	210	250	340	1,037	1,883
420570001260	700	2,800	317	360	450	390	1,060	125	220	280	380	1,097	2,290
420580001260	800	3,200	327	380	500	440	1,180	140	240	300	400	1,213	2,994
420590001260	900	3,600	338	400	520	460	1,260	150	260	320	420	1,282	3,565
420510001261	1,000	4,000	353	420	560	480	1,340	160	280	340	440	1,345	4,250
420512501261	1,250	5,000	371	450	600	530	1,415	185	310	360	480	1,452	5,500
420515501261	1,550	6,200	394	480	660	590	1,505	205	330	360	540	1,566	7,000

Traction Levage
marketingtl@traclev.com
© November 2026 - All Rights Reserved