Lifting Solutions Group
Axel Johnson International

ROV Hook RUD

Product information



- The RUD ROV-HOOK eliminates the risk of snagging and accidental rigging.
- The outer profile is smooth with no protruding hook nose.
- Outwards opening safety latch.
- The safety latch automatically closes when the ROV releases the triggers.
- The safety latch is securely locked in closed position.
- The hook can be operated by all commonly used ROV manipulators, including the grabber.
- The hook safety latch opening and closing can be operated by a single ROV manipulator.
- The hook design minimises the time the ROV takes to carry out the attachment/detachment operation.

... *Read more*

Material: Steel
Marking: According to standard, CE-mark, WLL
Temperature range: -20°C up to 200°C
Finish: Painted
Standard: EN 1677-1

Traction Levage
marketingtl@traclev.com

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

ROV Hook RUD

Technical data

Part code	Code	WLL ton	A mm	B mm	C mm	D mm	E mm	F mm	F max mm	G mm	H mm	T mm	Weight kg
401301001030	ROV-HOOK 2.0 10 t	10	112	45	45	55	166	65	99	38	82	393	13.7
401302501030	ROV-HOOK 2.0 25 t	25	132	55	55	92	249	96	130	52	82	484	26

Traction Levage
marketingtl@traclev.com

© November 2026 - All Rights Reserved