



ROV Hook RUD

Product information

- The RUD ROV-HOOK eliminates the risk of snagging and accidental rigging.
- The outer profile is smooth with no protruding hook nose.
- Outwards opening safety latch.
- The safety latch automatically closes when the ROV releases the triggers.
- The safety latch is securely locked in closed position.
- The hook can be operated by all commonly used ROV manipulators, including the grabber.
- The hook safety latch opening and closing can be operated by a single ROV manipulator.
- The hook design minimises the time the ROV takes to carry out the attachment/detachment operation.

Material: Steel

Marking: According to standard, CE-marked, WLL

Temperature range: -20°C up to 200°C

Finish: Painted

Standard: EN 1677-1

| Part code | Code | WLL ton | A mm | B mm | C mm | D mm | E mm | F mm | F max mm | G mm | H mm | T mm | Weight kg |
|--------------|-------------------|------------|------|------|------|---------|---------|---------|-------------|---------|---------|---------|--------------|
| 401301001030 | ROV-HOOK 2.0 10 t | 10 | 112 | 45 | 45 | 55 | 166 | 65 | 99 | 38 | 82 | 393 | 13.7 |
| 401302501030 | ROV-HOOK 2.0 25 t | 25 | 132 | 55 | 55 | 92 | 249 | 96 | 130 | 52 | 82 | 484 | 26 |