



## S Hook With Safety Latches On Both Sides 1620

### Product information

High quality S hook equipped with safety latches on both sides.

**Marking:** According to standard, CE-marked, Manufacturer sign, WLL, Date of Production MM/YY

**Temperature range:** -40°C up to +200°C

**Standard:** DIN EN 683-2

**Safety factor:** 4:1

**Grade:** 8

| <b>Part Code</b> | <b>WLL<br/>ton</b> | <b>A<br/>mm</b> | <b>B<br/>mm</b> | <b>C<br/>mm</b> | <b>D<br/>mm</b> | <b>Weight<br/>kg</b> |
|------------------|--------------------|-----------------|-----------------|-----------------|-----------------|----------------------|
| 420500011910     | 0.05               | 6               | 80              | 20              | 15              | 0.06                 |
| 420500011911     | 0.1                | 8               | 80              | 20              | 15              | 0.1                  |
| 420500021910     | 0.2                | 10              | 80              | 17              | 14              | 0.14                 |
| 420500031910     | 0.3                | 14              | 100             | 23              | 18              | 0.34                 |
| 420500051910     | 0.5                | 16              | 130             | 32              | 22              | 0.56                 |
| 420500081910     | 0.75               | 18              | 160             | 42              | 27              | 0.9                  |
| 420500101910     | 1                  | 20              | 180             | 48              | 37              | 1.2                  |
| 420500131910     | 1.25               | 22              | 200             | 51              | 38              | 1.5                  |
| 420500151910     | 1.5                | 26              | 220             | 55              | 50              | 2.3                  |
| 420500201910     | 2                  | 32              | 260             | 70              | 56              | 4.2                  |
| 420500301910     | 3                  | 36              | 320             | 84              | 65              | 6.4                  |
| 420500401910     | 4                  | 40              | 360             | 103             | 76              | 9                    |
| 420500501910     | 5                  | 45              | 400             | 110             | 76              | 13                   |

# Blueprint

