Lifting Solutions Group
Axel Johnson International

S Hook With Safety Latches On Both Sides 1620

Product information

High quality S hook equipped with safety latches on both sides.

... Read more



Marking: According to standard, CE-mark, Manufacturer sign, WLL, Date of Production MM/YY
Temperature range: -40°C up to +200°C
Standard: DIN EN 683-2

Safety factor: 4:1
Grade: 8


Traction Levage
marketingtl@traclev.com

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

S Hook With Safety Latches On Both Sides 1620

Blueprint



Technical data

Part code	WLL ton	A mm	B mm	C mm	D mm	Weight kg
420500011910	0.05	6	80	20	15	0.06
420500011911	0.1	8	80	20	15	0.1
420500021910	0.2	10	80	17	14	0.14
420500031910	0.3	14	100	23	18	0.34
420500051910	0.5	16	130	32	22	0.56
420500081910	0.75	18	160	42	27	0.9
420500101910	1	20	180	48	37	1.2
420500131910	1.25	22	200	51	38	1.5
420500151910	1.5	26	220	55	50	2.3
420500201910	2	32	260	70	56	4.2
420500301910	3	36	320	84	65	6.4
420500401910	4	40	360	103	76	9
420500501910	5	45	400	110	76	13

© November 2026 - All Rights Reserved