Lifting Solutions Group
Axel Johnson International

# Chain Block ROV with Fishtail, Tiger

**Product information**

This Chain Block is fully corrosion protected and specifically designed for the Offshore sector when used with Remotely Operated Vehicles (ROV). This product can have a WLL up to 30 tons.

Features of the ROV Chain Block:

- Subsea brake design with a patented Quad Cam pawl system
- 4 Point manipulator connection points
- Marine specific friction discs
- Specific Chain lengths to meet exact customer requirements
- Fluted chain stripper to guide the load chain efficiently
- Hook with an “EZ Check” to easily see if the hoist has been overloaded
- Each unit is fully tested and certified before delivery

This product is available with the following interfaces:

- Manual D Handle or T-bar
- Fishtail Direct Drive manual connection
- Rotary Torque Receptacle Classes 1,2 & 3
- Hydraulic Hot Stab connection dual port type A and B
- QD Direct Drive Couplings

Additional options are available:

- Chain carriers
- Heavy duty flexible Chain bag
- Stainless steel chain bucket
- Adaptor components
- Chain with extra corrosion protection is also available.

... *Read more*

**Material:** AISI 316 Framework and handle
**Marking:** CE-marked
**Note:** User manual supplied that includes a test certificate or an EC Declaration of Conformity. Chain certification is also included.

**Safety factor:** 4:1


© September 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

# Chain Block ROV with Fishtail, Tiger

## Blueprint




## Technical data

| Part code | WLL | Lifting height m | Number of falls | A mm | B mm | C mm | D mm | E mm | F1 mm mm | F2mm mm | G mm | H mm | M mm |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 5003RCB030F03 | 3 | 3 | 1 | 221 | 84 | 550 | 280 | 310 | 36 | 56 | 309 | 405 | 536 |
| 5003RCB060F03 | 6 | 3 | 2 | 221 | 84 | 703 | 214 | 376 | 49 | 70 | 309 | 467 | 536 |
| 5003RCB080F03 | 8 | 3 | 3 | 221 | 84 | 749 | 179 | 411 | 51 | 78 | 309 | 189 | 536 |
| 5003RCB100F03 | 10 | 3 | 3 | 221 | 84 | 660 | 185 | 405 | 54 | 87 | 309 | 515 | 536 |
| 5003RCB150F03 | 15 | 3 | 5 | 221 | 84 | 840 | 225 | 520 | 59 | 81 | 309 | 570 | 536 |
| 5003RCB200F03 | 20 | 3 | 6 | 221 | 90 | 1,050 | 148 | 515 | 81 | 110 | 309 | 650 | 542 |
| 5003RCB300F03 | 30 | 3 | 10 | 332 | 220 | 1,200 | 388 | 545 | 91 | 135 | 309 | 680 | 780 |

**Traction Levage**
marketingtl@traclev.com
© September 2026 - All Rights Reserved