

## The Original Roundsling Extreema® with HMPE core

### Product information



The Original Extreema® roundsling with HMPE core is a high-strength lifting sling developed for heavy lifting operations where low weight and durability are required. The parallel-laid HMPE fiber core ensures consistent load distribution and reliable performance. Combined with a cut-resistant HMPE sleeve, it is suited for demanding environments with increased risk of abrasion and damage.

Its core is made of general HMPE (Trosar®), which makes it up to 15 times stronger than steel on a weight-to-weight basis.

The sleeve is white HMPE Extreema® L-series sleeve. With exceptional performance against cuts, abrasions, and punctures. The white sleeve is repairable.

WLL range: 3t – 600t

EWL range: 0,5m – 65m

### When to choose this product

#### Best for:

- Heavy lifting requiring high strength with minimal sling weight
- Environments with abrasion, cutting risk, or chemical exposure

#### Product benefits:

- HMPE parallel-laid core provides high strength with low weight
- Cut-resistant HMPE sleeve protects against abrasion and punctures
- Does not absorb water and floats, suitable for marine use
- Chemical-resistant material supports use in harsh environments
- Repairable sleeve extends service life and reduces downtime
- RFID improve inspection and traceability

... [Read more](#)

**Material:** HMPE

**Marking:** CE-marked

**Temperature range:** -50°C up to +70°C

**Safety factor:** 7:1

## The Original Roundsling Extreema® with HMPE core

### Technical data

Part code	EWL m	WLL ton
340500300150170	1.5	3
340501000500170	5	10
340501000400170	4	10
340501000600170	6	10
340501001000170	10	10
340501501000170	10	15
340502000600170	6	20
340502301000170	10	23
340502500300170	3	25
340505001000170	10	50
340506000350170	3.5	60
340510000300170	3	100
340510001400170	14	100