Lifting Solutions Group
Axel Johnson International

# Turnbuckle Hook - Hook G-6312, Green Pin®

## Product information

The Green Pin® HH Turnbuckle is a turnbuckle with hook-hook end-fittings, generally to ASTM F1145-92. One of the unique features of Green Pin® Turnbuckles such as this one is that they can be used for both lifting and lashing. Galvanization of the Green Pin® HH Turnbuckle ensures its long-term durability. The turnbuckle is available in a range with a diameter thread of 3/8" (take up of 6") up to 1" (take up of 24").

Certification on request: 2.1, 2.2, 3.1, MTCa

**Standard:** Generally to ASTM F1145-92 formerly U.S. Federal Specification FF-T-791b.

... *Read more*

**Material:** Drop forged high tensile steel SAE 1035 or 1045.
**Marking:** CE-mark
**Temperature range:** -20°C up to +200°C
**Finish:** Hot dip galvanized.

**Safety factor:** 5:1

**Traction Levage**
marketingtl@traclev.com

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

# Turnbuckle Hook - Hook G-6312, Green Pin®

## Blueprint



## Technical data

| Part code | WLL ton | Thread | Take up inch | a" mm | b mm | c mm | d mm | e mm | f mm | g mm | Weight kg |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 422100540310 | 0.54 | 3/8 | 6 | 3/8 | 278 | 415 | 13 | 16 | 15 | 42 | 0.53 |
| 422100680310 | 0.68 | 1/2 | 12 | 1/2 | 456 | 739 | 13 | 19 | 16 | 47 | 1.34 |
| 422100100310 | 1 | 1/2 | 6 | 1/2 | 305 | 434 | 16 | 22 | 16 | 48 | 0.93 |
| 422100100315 | 1 | 1/2 | 9 | 1/2 | 380 | 587 | 16 | 22 | 16 | 47 | 1.16 |
| 422100140310 | 1.36 | 3/4 | 9 | 3/4 | 468 | 664 | 20 | 27 | 24 | 78 | 2.49 |
| 422100160310 | 1.59 | 5/8 | 6 | 5/8 | 356 | 479 | 16 | 23 | 21 | 67 | 1.4 |
| 422100160316 | 1.59 | 5/8 | 12 | 5/8 | 507 | 784 | 16 | 23 | 21 | 66 | 1.79 |
| 422100160315 | 1.59 | 5/8 | 9 | 5/8 | 431 | 632 | 20 | 24 | 21 | 66 | 1.96 |
| 422100230315 | 2.27 | 1 | 18 | 1 | 778 | 1,191 | 26 | 35 | 31 | 106 | 6.5 |
| 422100230316 | 2.27 | 1 | 24 | 1 | 928 | 1,495 | 26 | 35 | 31 | 105 | 8.13 |
| 422100240310 | 2.36 | 3/4 | 6 | 3/4 | 393 | 511 | 22 | 27 | 24 | 78 | 2.04 |
| 422100240315 | 2.36 | 3/4 | 12 | 3/4 | 544 | 816 | 22 | 27 | 24 | 78 | 3.27 |
| 422100450310 | 4.54 | 1 | 6 | 1 | 479 | 586 | 26 | 35 | 31 | 109 | 4.23 |
| 422100450315 | 4.54 | 1 | 12 | 1 | 625 | 886 | 26 | 35 | 31 | 106 | 6.64 |


© November 2026 - All Rights Reserved