



## Turnbuckles EH Eye - Hook Green Pin® G-6314

### Product information

The Green Pin® EH Turnbuckle is a turnbuckle with eye-hook end-fittings. One of the unique features of Green Pin® Turnbuckles such as this one is that they can be used for both lifting and lashing. Galvanization of the Green Pin® EE Turnbuckle ensures its long-term durability. The turnbuckle is available in a range with a diameter thread 3/8" (take up of 6") up to 1" (take up of 24").

Certification on request: 2.1, 2.2, 3.1, MTCa

**Standard:** generally to ASTM F1145-92 formerly U.S. Federal Specification FF-T-791b

**Material:** drop forged high tensile steel SAE 1035 or 1045

**Marking:** CE-marked

**Temperature range:** -20°C up to +200°C

**Finish:** hot dipped galvanized

**Safety factor:** 5:1

Part code	WLL ton	Thread	Take up inch	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	Weight kg
422100540330	0.54	3/8	6	285	422	13	16	15	10	13	29	49	0.47
422100680330	0.68	1/2	12	466	750	13	19	16	12	18	36	57	1.28
422100100330	1	1/2	6	315	445	16	22	16	12	18	36	58	0.82
422100100335	1	1/2	9	390	598	16	22	16	12	18	36	57	1.06
422100100336	1.02	5/8	6	368	491	16	23	21	14	21	45	79	1.31
422100100337	1.02	5/8	12	519	796	16	23	21	14	21	45	78	1.71
422100140330	1.36	3/4	9	479	675	20	27	24	17	26	54	89	4.49
422100160330	1.59	5/8	9	443	644	20	24	21	14	21	45	78	1.56
422100230330	2.27	1	6	488	595	26	35	31	24	36	75	118	3.87
422100230335	2.27	1	18	789	1,202	26	35	31	24	36	75	117	6
422100230336	2.27	1	24	939	1,506	26	35	31	24	36	75	116	7.52
422100240330	2.36	3/4	6	403	521	22	27	24	17	26	54	89	2.04
422100240335	2.36	3/4	12	554	827	22	27	24	17	26	54	88	2.3
422100240336	2.36	3/4	18	707	1,133	22	27	24	17	26	54	89	2.85
422100450330	4.54	1	12	636	897	26	35	31	24	36	75	117	5.09

# Blueprint

