Lifting Solutions Group
Axel Johnson International

Chain Hoist Rema® X-Line

Product information



The Rema® X-Line hand hoist is the solution for all demanding lifting tasks. With low operating force and increased safety system, you work efficiently and safely. The asbestos-free friction discs and wear-resistant load chain make use even more comfortable. The gradual bulging under overload and the orange powder coating provide additional safety and visibility. Available from 3 meters lifting height and 2.5 meters operating height, the Rema® X-Line hand hoist is suitable for any demanding task.

Properties

- Low operating force at full load.
- Increased operational safety due to double pawl system.
- Brake is provided with astbestos free friction discs.
- Load chain wheel is made of wear-resistant alloy steel.
- Top and bottom hook have safety latches.
- In case of overload, the hooks will gradually bend and do not suddenly break off.
- Galvanized load chain (Grade 8).
- Galvanized hand chain.
- Steel housing with orange colored powder coating.

Standard delivery

- 3 meters lifting height (max. between top and bottom hook).
- 2.5 meters operating height.

Option

- Available in any other hoisting and operational heights.

Norm:

- EN13100-1/2, EN13157, EN818-7

... *Read more*

Marking: According to standard, CE-mark
Standard: EN 13157, EN 818-7


Traction Levage
marketingtl@traclev.com

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Chain Hoist Rema® X-Line

Blueprint



Technical data

Part code	GTIN No.	WLL ton	Lifting height m	Number of falls	Model	Load chain mm	Hand chain mm	Construction height mm	Hand force max. kg	A mm	B mm	C mm	D mm	H mm	Weight kg
50010170000	8717365112416	0.25	-	1	X-CH025/250KG	4.0 x 12	5.0 x 23.7	260	23.5	108	106	20	30	260	6
500101700003	8717365112539	0.25	3	1	X-CH/250KG/3M	4.0 x 12	5.0 x 23.7	260	23.5	108	106	20	30	260	6
500101700004	8717365112423	0.25	4	1	X-CH/250KG/4M	4.0 x 12	5.0 x 23.7	260	23.5	108	106	20	30	260	7.4
500101700005	8717365112430	0.25	5	1	X-CH/250KG/5M	4.0 x 12	5.0 x 23.7	260	23.5	108	106	20	30	260	8.8
500101700006	8717365112553	0.25	6	1	X-CH/250KG/6M	4.0 x 12	5.0 x 23.7	260	23.5	108	106	20	30	260	10.2
500101700007	8717365112447	0.25	7	1	X-CH/250KG/7M	4.0 x 12	5.0 x 23.7	260	23.5	108	106	20	30	260	11.6
500101700008	8717365112454	0.25	8	1	X-CH/250KG/8M	4.0 x 12	5.0 x 23.7	260	23.5	108	106	20	30	260	13
500101700009	8717365112461	0.25	9	1	X-CH/250KG/9M	4.0 x 12	5.0 x 23.7	260	23.5	108	106	20	30	260	14.4
5001017000010	8717365112478	0.25	10	1	X-CH/250KG/10M	4.0 x 12	5.0 x 23.7	260	23.5	108	106	20	30	260	15.8
50010170001	8717365088506	0.5	-	1	X-CH05/500KG	5.0 x 15	5.0 x 23.7	280	24.9	130	128	22	34	280	9
500101700013	8717365096211	0.5	3	1	X-CH/500KG/3M	5.0 x 15	5.0 x 23.7	280	24.9	130	128	22	34	280	10
500101700014	8717365096440	0.5	4	1	X-CH/500KG/4M	5.0 x 15	5.0 x 23.7	280	24.9	130	128	22	34	280	11.6
500101700015	8717365096457	0.5	5	1	X-CH/500KG/5M	5.0 x 15	5.0 x 23.7	280	24.9	130	128	22	34	280	13.2
500101700016	8717365096228	0.5	6	1	X-CH/500KG/6M	5.0 x 15	5.0 x 23.7	280	24.9	130	128	22	34	280	14.8
500101700017	8717365096464	0.5	7	1	X-CH/500KG/7M	5.0 x 15	5.0 x 23.7	280	24.9	130	128	22	34	280	16.4
500101700018	8717365096471	0.5	8	1	X-CH/500KG/8M	5.0 x 15	5.0 x 23.7	280	24.9	130	128	22	34	280	18
500101700019	8717365096488	0.5	9	1	X-CH/500KG/9M	5.0 x 15	5.0 x 23.7	280	24.9	130	128	22	34	280	19.6
5001017000110	8717365096495	0.5	10	1	X-CH/500KG/10M	5.0 x 15	5.0 x 23.7	280	24.9	130	128	22	34	280	21.2
50010170003	8717365088513	1	-	1	X-CH10/1000KG	6.3 x 19	5.0 x 23.7	330	28.4	150	142	26	39	330	12
500101700033	8717365096235	1	3	1	X-CH/1000KG/3M	6.3 x 19	5.0 x 23.7	330	28.4	150	142	26	39	330	12
500101700034	8717365096501	1	4	1	X-CH/1000KG/4M	6.3 x 19	5.0 x 23.7	330	28.4	150	142	26	39	330	13.9
500101700035	8717365096518	1	5	1	X-CH/1000KG/5M	6.3 x 19	5.0 x 23.7	330	28.4	150	142	26	39	330	15.8

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Chain Hoist Rema® X-Line

Technical data

Part code	GTIN No.	WLL ton	Lifting height m	Number of falls	Model	Load chain mm	Hand chain mm	Construction height mm	Hand force max. kg	A mm	B mm	C mm	D mm	H mm	Weight kg
500101700036	8717365096242	1	6	1	X-CH/1000KG/6M	6.3 x 19	5.0 x 23.7	330	28.4	150	142	26	39	330	17.7
500101700037	8717365096525	1	7	1	X-CH/1000KG/7M	6.3 x 19	5.0 x 23.7	330	28.4	150	142	26	39	330	19.6
500101700038	8717365096532	1	8	1	X-CH/1000KG/8M	6.3 x 19	5.0 x 23.7	330	28.4	150	142	26	39	330	21.5
500101700039	8717365096549	1	9	1	X-CH/1000KG/9M	6.3 x 19	5.0 x 23.7	330	28.4	150	142	26	39	330	23.4
5001017000310	8717365096556	1	10	1	X-CH/1000KG/10M	6.3 x 19	5.0 x 23.7	330	28.4	150	142	26	39	330	25.3
50010170005	8717365088520	1.5	-	1	X-CH15/1500KG	7.1 x 21	5.0 x 23.7	360	30.8	170	158	29	42	360	16
500101700053	8717365096259	1.5	3	1	X-CH/1500KG/3M	7.1 x 21	5.0 x 23.7	360	30.8	170	158	29	42	360	16
500101700054	8717365096563	1.5	4	1	X-CH/1500KG/4M	7.1 x 21	5.0 x 23.7	360	30.8	170	158	29	42	360	18.2
500101700055	8717365096570	1.5	5	1	X-CH/1500KG/5M	7.1 x 21	5.0 x 23.7	360	30.8	170	158	29	42	360	20.4
500101700056	8717365096266	1.5	6	1	X-CH/1500KG/6M	7.1 x 21	5.0 x 23.7	360	30.8	170	158	29	42	360	22.6
500101700057	8717365096587	1.5	7	1	X-CH/1500KG/7M	7.1 x 21	5.0 x 23.7	360	30.8	170	158	29	42	360	24.8
500101700058	8717365096594	1.5	8	1	X-CH/1500KG/8M	7.1 x 21	5.0 x 23.7	360	30.8	170	158	29	42	360	27
500101700059	8717365096600	1.5	9	1	X-CH/1500KG/9M	7.1 x 21	5.0 x 23.7	360	30.8	170	158	29	42	360	29.2
5001017000510	8717365096617	1.5	10	1	X-CH/1500KG/10M	7.1 x 21	5.0 x 23.7	360	30.8	170	158	29	42	360	31.4
50010170007	8717365088537	2	-	1	X-CH20/2000KG	8.0 x 24	5.0 x 23.7	385	34.3	185	175	35	49	385	20
500101700073	8717365096273	2	3	1	X-CH/2000KG/3M	8.0 x 24	5.0 x 23.7	385	34.3	185	175	35	49	385	20
500101700074	8717365096624	2	4	1	X-CH/2000KG/4M	8.0 x 24	5.0 x 23.7	385	34.3	185	175	35	49	385	22.4
500101700075	8717365096631	2	5	1	X-CH/2000KG/5M	8.0 x 24	5.0 x 23.7	385	34.3	185	175	35	49	385	24.8
500101700076	8717365096280	2	6	1	X-CH/2000KG/6M	8.0 x 24	5.0 x 23.7	385	34.3	185	175	35	49	385	27.2
500101700077	8717365096648	2	7	1	X-CH/2000KG/7M	8.0 x 24	5.0 x 23.7	385	34.3	185	175	35	49	385	29.6
500101700078	8717365096655	2	8	1	X-CH/2000KG/8M	8.0 x 24	5.0 x 23.7	385	34.3	185	175	35	49	385	32
500101700079	8717365096662	2	9	1	X-CH/2000KG/9M	8.0 x 24	5.0 x 23.7	385	34.3	185	175	35	49	385	34.4
5001017000710	8717365096679	2	10	1	X-CH/2000KG/10M	8.0 x 24	5.0 x 23.7	385	34.3	185	175	35	49	385	36.8
50010170009	8717365088544	3	-	2	X-CH30/3000KG	7.1 x 21	5.0 x 23.7	510	34.3	220	158	37	50	510	24
500101700093	8717365096297	3	3	2	X-CH/3000KG/3M	7.1 x 21	5.0 x 23.7	510	34.3	220	158	37	50	510	26
500101700094	8717365096686	3	4	2	X-CH/3000KG/4M	7.1 x 21	5.0 x 23.7	510	34.3	220	158	37	50	510	29.4
500101700095	8717365096693	3	5	2	X-CH/3000KG/5M	7.1 x 21	5.0 x 23.7	510	34.3	220	158	37	50	510	32.8
500101700096	8717365096303	3	6	2	X-CH/3000KG/6M	7.1 x 21	5.0 x 23.7	510	34.3	220	158	37	50	510	36.2
500101700097	8717365096709	3	7	2	X-CH/3000KG/7M	7.1 x 21	5.0 x 23.7	510	34.3	220	158	37	50	510	39.6

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Chain Hoist Rema® X-Line

Technical data

Part code	GTIN No.	WLL ton	Lifting height m	Number of falls	Model	Load chain mm	Hand chain mm	Construction height mm	Hand force max. kg	A mm	B mm	C mm	D mm	H mm	Weight kg
500101700098	8717365096716	3	8	2	X-CH/3000KG/8M	7.1 x 21	5.0 x 23.7	510	34.3	220	158	37	50	510	43
500101700099	8717365096723	3	9	2	X-CH/3000KG/9M	7.1 x 21	5.0 x 23.7	510	34.3	220	158	37	50	510	46.4
5001017000910	8717365096730	3	10	2	X-CH/3000KG/10M	7.1 x 21	5.0 x 23.7	510	34.3	220	158	37	50	510	49.8
50010170011	8717365088551	5	-	2	X-CH50/5000KG	9.0 x 27	5.0 x 23.7	615	37.2	255	183	43	60	615	37
500101700113	8717365096310	5	3	2	X-CH/5000KG/3M	9.0 x 27	5.0 x 23.7	615	37.2	255	183	43	60	615	41.5
500101700114	8717365096747	5	4	2	X-CH/5000KG/4M	9.0 x 27	5.0 x 23.7	615	37.2	255	183	43	60	615	46
500101700115	8717365096754	5	5	2	X-CH/5000KG/5M	9.0 x 27	5.0 x 23.7	615	37.2	255	183	43	60	615	50.5
500101700116	8717365096327	5	6	2	X-CH/5000KG/6M	9.0 x 27	5.0 x 23.7	615	37.2	255	183	43	60	615	55
500101700117	8717365096761	5	7	2	X-CH/5000KG/7M	9.0 x 27	5.0 x 23.7	615	37.2	255	183	43	60	615	59.5
500101700118	8717365096778	5	8	2	X-CH/5000KG/8M	9.0 x 27	5.0 x 23.7	615	37.2	255	183	43	60	615	64
500101700119	8717365096785	5	9	2	X-CH/5000KG/9M	9.0 x 27	5.0 x 23.7	615	37.2	255	183	43	60	615	68.5
5001017001110	8717365096792	5	10	2	X-CH/5000KG/10M	9.0 x 27	5.0 x 23.7	615	37.2	255	183	43	60	615	73
50010170015	8717365088636	10	-	4	X-CH100/10000KG	9.0 x 27	5.0 x 23.7	820	40	360	183	47	65	820	68
500101700153	8717365096433	10	3	4	X-CH/10000KG/3M	9.0 x 27	5.0 x 23.7	820	40	360	183	47	65	820	75
500101700154	8717365096808	10	4	4	X-CH/10000KG/4M	9.0 x 27	5.0 x 23.7	820	40	360	183	47	65	820	83
500101700155	8717365096815	10	5	4	X-CH/10000KG/5M	9.0 x 27	5.0 x 23.7	820	40	360	183	47	65	820	91
500101700156	8717365096426	10	6	4	X-CH/10000KG/6M	9.0 x 27	5.0 x 23.7	820	40	360	183	47	65	820	99
500101700157	8717365096822	10	7	4	X-CH/10000KG/7M	9.0 x 27	5.0 x 23.7	820	40	360	183	47	65	820	107
500101700158	8717365096839	10	8	4	X-CH/10000KG/8M	9.0 x 27	5.0 x 23.7	820	40	360	183	47	65	820	115
500101700159	8717365096846	10	9	4	X-CH/10000KG/9M	9.0 x 27	5.0 x 23.7	820	40	360	183	47	65	820	123
5001017001510	8717365096853	10	10	4	X-CH/10000KG/10M	9.0 x 27	5.0 x 23.7	820	40	360	183	47	65	820	131

© November 2026 - All Rights Reserved