



Double Swivel Ring Codipro OS DSR UP

Product information

The OS DSR UP offshore lifting ring is a double swivel ring. It is specially designed for simultaneously lifting and rotating loads. Its double swivel action ensures perfect alignment with the sling. The ring swivels 180° but has a rotating range of 360°. All DSR offshore lifting rings models have a safety factor of 4 and 5, which means that their breaking load is four or five times greater than the capacity indicated in the technical sheet.

Material: High tensile steel

Marking: According to standard, CE-marked

Temperature range: -20°C up to +200°C

Finish: Lamellar coating

Standard: EN 1677-1

Safety factor: 5:1

| Part code | WLL ton | Thread mm | Torque Nm | L1 mm | S1 mm | S2 mm | A mm | B mm | C mm | D mm | E mm | F mm | G mm | H mm | Weight kg |
|-------------------|------------|--------------|--------------|-------|-------|-------|------|------|------|---------|---------|---------|---------|------|--------------|
| 4215OSDSRM10UP | 0.7 | M 10 | 10 | 18 | 8 | 16 | 33 | 30 | 30 | 38 | 27 | 14 | 53 | 9.5 | 0.3 |
| 4215OSDSRM12UP | 1.05 | M 12 | 15 | 21 | 8 | 16 | 33 | 30 | 30 | 38 | 27 | 14 | 53 | 9.5 | 0.3 |
| 4215OSDSRM16UP | 2 | M 16 | 50 | 27 | 8 | 20 | 45 | 40 | 45 | 53 | 38 | 17 | 76 | 13 | 0.9 |
| 4215OSDSRM2031UP | 2.9 | M 20 | 100 | 25 | 14 | 24 | 62 | 55 | 60 | 83 | 55 | 25 | 115 | 19 | 2.6 |
| 4215OSDSRM24UP | 4.4 | M 24 | 160 | 36 | 14 | 24 | 62 | 55 | 60 | 83 | 55 | 25 | 115 | 19 | 2.6 |
| 4215OSDSRM306t3UP | 6 | M 30 | 250 | 45 | 14 | 24 | 62 | 55 | 60 | 83 | 55 | 25 | 115 | 19 | 2.7 |

Technical data



Blueprint

