

Rope tensioner TIRVIT™

Product information



The TIRVIT™ is hand-operated pulling wire tensioner. It is versatile, portable and multi-purpose, not only for pulling but also for tensioning. The originality of the TIRVIT™ universal wire tensioner, is the principle of operation directly on the wire rope which passes through the mechanism rather than being reeled onto a drum of a hoist or conventional winch. The pull is applied by means of two pairs of selfenergised jaws which exert a grip on the wire rope in proportion to the load being pulled. An operating lever transmits the effort to the jaw mechanism to forward movement of the wire rope.

Fast and easy tensioning of wire ropes such as electric transport cables, telephone cables and fence assembly. Also suitable for pulling loads. Not suitable for lifting.

- Complete with mounting chain
- Suitable for tensioning wire ropes
- Suitable for pulling loads

Warning: Do not use to lift people! Do not attempt to motorise the model!

| Part code | Code | Rope Ø range mm | WLL ton | A mm | B mm | C mm | Weight kg |
|-----------|------|-----------------|---------|------|------|------|-----------|
| 12981029 | F2 | 6-8 | 0.4 | 535 | 88 | 653 | 4 |
| 12981039 | F3 | 7-15 | 0.6 | 625 | 110 | 730 | 5.2 |
| 12981049 | F4 | 14-18 | 0.8 | 625 | 115 | 720 | 6.5 |

Blueprint

