Lifting Solutions Group
Axel Johnson International

Lifting Clamp for Beam Profiles PL

Product information



Lifting clamp for lifting I or H beams. Automatic release and handle for easy use. These accessories are equipped with an open position locking system, allowing the load to be set down without any intervention on the clamp. The upper arm features an ergonomic handle for easier grip and a safety system that prevents the complete closure of the parallelogram. This provides better protection for the hands.

Lifting Clamp For Beam Profiles PL fulfill the Machinery Directive 2006/42/EC

... *Read more*

Marking: CE-marked
Temperature range: -20° up to 90°C
Finish: Hot epoxy coating
Warning: Never transport people using this equipment! Only for vertical traction


Traction Levage
marketingtl@traclev.com

© October 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Lifting Clamp for Beam Profiles PL

Blueprint



Technical data

Part code	Code	WLL ton	Jaw width mm	A mm	B mm	B' mm mm	C mm	D mm	E mm	F mm	G mm	H mm	I mm	J mm	K mm	L mm	Weight kg
502100102001960	PL1 95-200	1	95-200	182-348	166-174	73-135	284-504	18	52	69	12	95	22	230	46-48	3	4
502100203001960	PL2 120-300	2	120-300	196-462	167-176	76-140	348-604	23	64	80	20	119	50	330	30-30	3	8
502100304501960	PL3 180-450	3	180-450	296-627	200-205	102-182	435-768	36	74	92	25	143	61	420	23-56	3	16
502100403001960	PL4 120-300	4	120-300	196-444	173-173	75-139	398-622	36	74	92	25	147	74	310	30-30	3	14

© October 2026 - All Rights Reserved