

Lifting Clamp for Rail Profile PR

Product information



Lifting clamp for vertically lifting rail profiles (vignoles rail). Default automatic release.

Features:

- Ergonomic handle
- Semi-automatic
- Developed especially for vertically lifting rails

Lifting Clamp For Rail Profile PR fulfill the Machinery Directive 2006/42/EC. [... Read more](#)

Material: Manufactured without load bearing welds

Marking: CE-marked

Temperature range: -20° up to 90°C


Finish: Hot epoxy coating

Note: Recommended use: in pairs

Warning: Never transport people using this equipment! Only for vertical traction

Lifting Clamp for Rail Profile PR

Blueprint



Technical data

| Part code | Code | WLL ton | Jaw width mm | A mm | B mm | B' mm mm | D mm | E mm | F mm | G mm | H mm | I mm | J mm | K mm | L mm | Weight kg |
|-----------------|------------|---------|--------------|---------|---------|----------|---------|------|---------|------|------|------|------|------|------|-----------|
| 502100100401830 | PR1 20-40 | 1 | 20-40 | 292-318 | 95-124 | 158-176 | 174-190 | 40 | 65-80 | 69 | 52 | 18 | 12 | 95 | 22 | 4 |
| 502100200801830 | PR2 40-80 | 2 | 40-80 | 385-432 | 103-142 | 189-202 | 247-315 | 50 | 106-135 | 80 | 64 | 23 | 20 | 126 | 32 | 9 |
| 502100200801834 | PR2A 40-80 | 2 | 40-80 | 385-432 | 103-142 | 189-202 | 247-315 | 50 | 106-135 | 80 | 64 | 23 | 20 | 126 | 32 | 10.2 |