Lifting Solutions Group
Axel Johnson International

# Lifting Clamp for Rail Profile PR

**Product information**



Lifting clamp for vertically lifting rail profiles (vignoles rail). Default automatic release.

**Features:**

- Ergonomic handle
- Semi-automatic
- Developed especially for vertically lifting rails

Lifting Clamp For Rail Profile PR fulfill the Machinery Directive 2006/42/EC

... *Read more*

**Material:** Manufactured without load bearing welds
**Marking:** CE-marked
**Temperature range:** -20° up to 90°C
**Finish:** Hot epoxy coating
**Note:** Recommended use: in pairs
**Warning:** Never transport people using this equipment! Only for vertical traction


**Traction Levage**
marketingtl@traclev.com

© October 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

# Lifting Clamp for Rail Profile PR

## Blueprint



## Technical data

| Part code | Code | WLL ton | Jaw width mm | A mm | B mm | B' mm mm | D mm | E mm | F mm | G mm | H mm | I mm | J mm | K mm | L mm | Weight kg |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 502100100401830 | PR1 20-40 | 1 | 20-40 | 292-318 | 95-124 | 158-176 | 174-190 | 40 | 65-80 | 69 | 52 | 18 | 12 | 95 | 22 | 4 |
| 502100200801830 | PR2 40-80 | 2 | 40-80 | 385-432 | 103-142 | 189-202 | 247-315 | 50 | 106-135 | 80 | 64 | 23 | 20 | 126 | 32 | 9 |
| 502100200801834 | PR2A 40-80 | 2 | 40-80 | 385-432 | 103-142 | 189-202 | 247-315 | 50 | 106-135 | 80 | 64 | 23 | 20 | 126 | 32 | 10.2 |


© October 2026 - All Rights Reserved