



Electric Chain Hoist LIFTKET STAR 125 – 2.000 kg

Product information

The LIFTKET product portfolio offers you standardized hoists that can be adjusted to your requirements in a modular way, as well as highly specialized solutions. Larger lifting and operating heights are just as viable as deviating voltages and special solutions of any kind.

Features:

- Power supply 220 - 240 V, 1 phase, 50 Hz
- From 125 kg to 2.000 kg we lift everything that moves you
- FEM ratings from Fem 1Bm to 4m (ISO M3 to M7)
- Protection class IP55, insulation class F
- Galvanized load chain to DIN 818-7 quality class DAT
- A wide range of options can be selected as standard
- Optional one or two lifting speeds from 2 to 32 m/min.
- With heavy-duty end position switch-off as standard (at 24VAC)
- Up to 200 meters high safely and anywhere
- Patented safety-brake-clutch system
- Modular hoist design
- Simply and cost effective maintenance and repair
- A unique ID makes it possible to trace exactly when a particular electric chain hoist was built by whom and with which materials – even after 10 years

Trolleys/Boogies: Manual or electric trolleys in various designs for each steel section girder.

Also available for the food industry:

The models of the STAR LIFTKET Foodline are equipped with a stainless steel load chain according to AISI 316 and a safety factor of min. 5:1. In addition, the NSF-H1 lubricant approved for the food industry is standard equipment in the gearbox. Optionally, the chain hoists can be ordered with stainless steel load hooks

Marking: CE-marked

Note: Standard version delivered with lifting eye (connection between crane and trolley). Alternatively, comes with suspension hook. Standard stock hoist with 6 m lifting height.

Part code	Code	WLL ton	Lifting height m	Lifting speed m/min	Number of falls	Motor kW	Duty rating % ED	Class ISO/FEM	Load chain mm	A mm	B mm	C mm	G, mm	G2 mm	mm	øN mm	mm	J mm	Weight kg
540101251470290	030/01	0.125	3	8	1	0.35	25	M3/1Bm	5.2x15	212	192	220	365	409		37		20	18
540101251470296	031/53	0.125	6	8	1	0.35	25	M3/1Bm	5.2x15	212	192	220	380	406		25		20	31
540100031470290	030/01	0.25	3	8	1	0.35	25	M3/1Bm	5.2x15	212	192	220	365	409		37		20	18
540100031470296	030/01	0.25	6	8	1	0.35	25	M3/1Bm	5.2x15	212	192	220	380	406		25		20	23
540100052250290	030/01	0.5	3	4	2	0.35	25	M3/1Bm	5.2x15	212	192	220	413	454		37		22	21
540100051470290	050/02	0.5	3	8	1	0.7	25	M3/1Bm	5.2x15	266	232	274	388	496		37		20	33
540100102250290	050/02	1	3	4	2	0.7	25	M3/1Bm	5.2x15	266	232	274	436	508		37		22	36
540100101340290	070/01	1	3	6	1	1.1	25	M3/1Bm	7.2x21	266	232	274	413	460		47		22	36
540100161470296	090/55	1.6	6	8	1	2.2	25	2m/2m	9x27	359	283	359	488	548		-		30	70
540100202190290	070/01	2	3	3	2	1.1	25	M3/1Bm	7.2x21	266	232	274	514	561		47		28	41

Technical data

Blueprint

