

## Flat webbing sling

### Product information



**General:** Flat webbing sling with simple eye – B type – Category 1

Identification : flat webbing sling in woven webbing

Type : Double ply (B type)

Configuration : Flexible sling consisting of a single element in sewn webbing

Endings : Simple eyes, category 1.

Traceability : High resisting blue pvc label sewn on the sling.

Instructions of use : Ensure that sling is protected from any sharp corners and/or abrasive surfaces, use either protective polyester, polyurethane sleeves or coatings. DO NOT USE DAMAGED SLINGS.

Storage : Store in a cool, dry and protected from sunlight area.

Maintenance : Never dry sling near a fire or any source of heat.

**Design:** Textile sleeve, 100% polyester, sewn around each eye to reinforce and protect its inner surface

**Stretch with working Load:** for textile slings

**Length Tolerance:** A

**Material:** 100% polyester multifilament fibres of high tenacity

**Marking:** According to standard, Manufacturer's symbol, working load limit (WLL), effective working length, CE marking, batch number, handling instructions.

**Temperature range:** From -40°C to +100°C.

**Standard:** EN 1492-1

Part Code	WLL ton
27986	0.5
9878	1
-	1.5
22131	2
-	2.5
-	3
-	4
-	5
-	6
-	8
-	10

## Blueprint

