

## Flat webbing sling with folded eye

### Product information



**General:** Flat webbing sling with folded eye – B type – Category 2

**Identification:** Flat webbing sling in woven webbing.

**Type:** Double ply (B type)

**Configuration:** Flexible sling consisting of a single element in sewn webbing.

**Endings:** Folded eyes, category 2.

Ensure that sling is protected from any sharp corners and/or abrasive surfaces, use either protective polyester, polyurethane sleeves or coatings. DO NOT USE DAMAGED SLINGS.

**Storage:** Store in a cool, dry and protected from sunlight area.

**Maintenance:** Never dry sling near a fire or any source of heat.

**Design:** Textile sleeve, 100% polyester, sewn around each eye to reinforce and protect its inner surface. High resisting blue pvc label sewn on the sling.

**Material:** 100% polyester multifilament fibres of high tenacity.

**Marking:** According to standard, manufacturer's symbol, working load limit (WLL), effective working length, CE marking, batch number, handling instructions.

**Temperature range:** From -40°C to +100°C.

**Standard:** EN 1492-1

### Part code

### WLL ton

341100050100140

0.5

341100050150140

0.5

341100050200140

0.5

341100050250140

0.5

341100050300140

0.5

341100050400140	0.5
341100050500140	0.5
341100050600140	0.5
341100050700140	0.5
341100050800140	0.5
341100050900140	0.5
341100051000140	0.5
341100100100140	1
341100100150140	1
341100100200140	1
341100100250140	1
341100100300140	1
341100100400140	1
341100100500140	1
341100100600140	1
341100100700140	1
341100100800140	1
341100100900140	1
341100101000140	1
341100150100140	1.5
341100150150140	1.5
341100150200140	1.5
341100150250140	1.5

341100150300140	1.5
341100150400140	1.5
341100150500140	1.5
341100150600140	1.5
341100150700140	1.5
341100150800140	1.5
341100150900140	1.5
341100151000140	1.5
341100200100140	2
341100200150140	2
341100200200140	2
341100200250140	2
341100200300140	2
341100200400140	2
341100200500140	2
341100200600140	2
341100200700140	2
341100200800140	2
341100200900140	2
341100201000140	2

## Blueprint

