

Flat webbing – B type – Category 6

Product information



General: Identification : flat webbing sling in woven webbing
 Type : Double ply (B type)
 Configuration : Flexible sling consisting of a single element in sewn webbing
 Endings : 2 torch cut male rings, category 6.

Traceability : High resisting blue pvc label sewn on the sling.
 Instructions of use : Ensure that sling is protected from any sharp corners and/or abrasive surfaces, use either protective polyester, polyurethane sleeves or coatings. **DO NOT USE DAMAGED SLINGS.**
 Storage : Store in a cool, dry and protected from sunlight area.
 Maintenance : Never dry sling near a fire or any source of heat.

Design: Textile sleeve, 100% polyester, sewn at the two endings to reinforce and protect the eyes

Material: 100% polyester multifilament fibers of high tenacity
Marking: According to standard, Manufacturer's symbol, working load limit (WLL), effective working length, CE marking, batch number, handling instructions.
Temperature range: From -40°C to +100°C.
Standard: EN 1492-1

Part code	EWL m	WLL ton	Webbing width mm	Thickness mm	Colour	Weight kg
341100400100170	1	4	120	7	Grey	6.1

341100400150170	1.5	4	120	7	Grey	7.3
341100400200170	2	4	120	7	Grey	7.7
341100400250170	2.5	4	120	7	Grey	8.1
341100400300170	3	4	120	7	Grey	8.5
341100400400170	4	4	120	7	Grey	9.3
341100400500170	5	4	120	7	Grey	10.1
341100400600170	6	4	120	7	Grey	10.9
341100400700170	7	4	120	7	Grey	11.7
341100400800170	8	4	120	7	Grey	12.5
341100400900170	9	4	120	7	Grey	13.3
341100401000170	10	4	120	7	Grey	14.1
341100500100170	1	5	150	7.5	Red	7.85
341100500150170	1.5	5	150	7.5	Red	9.35
341100500200170	2	5	150	7.5	Red	9.85
341100500250170	2.5	5	150	7.5	Red	10.35
341100500300170	3	5	150	7.5	Red	10.85
341100500400170	4	5	150	7.5	Red	11.85
341100500500170	5	5	150	7.5	Red	12.85
341100500600170	6	5	150	7.5	Red	13.85
341100500700170	7	5	150	7.5	Red	14.85
341100500800170	8	5	150	7.5	Red	15.85
341100500900170	9	5	150	7.5	Red	16.85
341100501000170	10	5	150	7.5	Red	17.85

341100600100170	1	6	180	7.5	Brown	11.4
341100600150170	1.5	6	180	7.5	Brown	13.2
341100600200170	2	6	180	7.5	Brown	13.8
341100600250170	2.5	6	180	7.5	Brown	14.4
341100600300170	3	6	180	7.5	Brown	15
341100600400170	4	6	180	7.5	Brown	16.2
341100600500170	5	6	180	7.5	Brown	17.4
341100600600170	6	6	180	7.5	Brown	18.6
341100600700170	7	6	180	7.5	Brown	19.8
341100600800170	8	6	180	7.5	Brown	21
341100600900170	9	6	180	7.5	Brown	22.2
341100601000170	10	6	180	7.5	Brown	23.4
341100800100170	1	8	240	8	Blue	22.8
341100800150170	1.5	8	240	8	Blue	25.35
341100800200170	2	8	240	8	Blue	26.2
341100800250170	2.5	8	240	8	Blue	27.05
341100800300170	3	8	240	8	Blue	27.9
341100800400170	4	8	240	8	Blue	29.6
341100800500170	5	8	240	8	Blue	31.3
341100800600170	6	8	240	8	Blue	33
341100800700170	7	8	240	8	Blue	34.7
341100800800170	8	8	240	8	Blue	36.4
341100800900170	9	8	240	8	Blue	38.1

341100801000170	10	8	240	8	Blue	39.8
341101000100170	1	10	300	8	Orange	28.75
341101000150170	1.5	10	300	8	Orange	32.13
341101000200170	2	10	300	8	Orange	33.25
341101000250170	2.5	10	300	8	Orange	34.38
341101000300170	3	10	300	8	Orange	35.5
341101000400170	4	10	300	8	Orange	37.75
341101000500170	5	10	300	8	Orange	40
341101000600170	6	10	300	8	Orange	42.25
341101000700170	7	10	300	8	Orange	44.5
341101000800170	8	10	300	8	Orange	46.75
341101000900170	9	10	300	8	Orange	49
341101001000170	10	10	300	8	Orange	51.25

Technical data

Male buckle for flat webbing sling Cat. 6					
WLL (tons)	4	5	6	8	10
A (mm)	85	85	105	114	107
B (mm)	110	110	120	145	141
C (mm)	29	27	30	44	48
D (mm)	137	158	198	252	305
E (mm)	18	20	20	20	25
F (mm)	178	198	258	328	390
G (mm)	148	155	170	210	212

Blueprint

