

Webbing slings 0,5 - 12 t

Product information



Double layer Duplex webbing slings 0,5 - 12 t. Folded reinforced eyes as standard and also available with flat eye. Color coded.

Thanks to our own production unit, we can also make quick deliveries of special types and lengths as well as lifting slings with higher WLL up to 12t.

... [Read more](#)

Material: Polyester

Note: Standard dimensional tolerance is $\pm 3\%$. Lengths can vary within the tolerance range!

Webbing slings 0,5 - 12 t

Technical data

| Part code | EWL | WLL ton | Choke Hitch ton | Basket Hitch 0° ton | Basket Hitch 0-45° ton | Basket Hitch 45°-60° ton | Webbing width mm | Colour |
|-----------|-----|---------|-----------------|---------------------|------------------------|--------------------------|------------------|--------|
| 41020027F | 1 | 1 | 0.8 | 2 | 1.4 | 1 | 50 | Violet |
| 41020035F | 2 | 1 | 0.8 | 2 | 1.4 | 1 | 50 | Violet |
| 41020042F | 3 | 1 | 0.8 | 2 | 1.4 | 1 | 50 | Violet |
| 41020046F | 4 | 1 | 0.8 | 2 | 1.4 | 1 | 50 | Violet |
| 41020050F | 5 | 1 | 0.8 | 2 | 1.4 | 1 | 50 | Violet |
| 41020052F | 6 | 1 | 0.8 | 2 | 1.4 | 1 | 50 | Violet |
| 41020055F | 8 | 1 | 0.8 | 2 | 1.4 | 1 | 50 | Violet |
| 41020058F | 10 | 1 | 0.8 | 2 | 1.4 | 1 | 50 | Violet |
| 41020079F | 2 | 2 | 1.6 | 4 | 2.8 | 2 | 60 | Green |
| 41020084F | 4 | 2 | 1.6 | 4 | 2.8 | 2 | 60 | Green |
| 41020087F | 5 | 2 | 1.6 | 4 | 2.8 | 2 | 60 | Green |
| 41020088F | 6 | 2 | 1.6 | 4 | 2.8 | 2 | 60 | Green |
| 41020100F | 3 | 3 | 2.4 | 6 | 4.2 | 3 | 90 | Yellow |
| 41020103F | 4 | 3 | 2.4 | 6 | 4.2 | 3 | 90 | Yellow |
| 41020110F | 6 | 3 | 2.4 | 6 | 4.2 | 3 | 90 | Yellow |
| 41020127F | 3 | 4 | 3.2 | 8 | 5.6 | 4 | 120 | Grey |
| 41020128F | 4 | 4 | 3.2 | 8 | 5.6 | 4 | 120 | Grey |
| 41020130F | 6 | 4 | 3.2 | 8 | 5.6 | 4 | 120 | Grey |
| 41020140F | 2 | 5 | 4 | 10 | 7 | 5 | 150 | Red |
| 41020144F | 4 | 5 | 4 | 10 | 7 | 5 | 150 | Red |
| 41020145F | 5 | 5 | 4 | 10 | 7 | 5 | 150 | Red |
| 41020147F | 8 | 5 | 4 | 10 | 7 | 5 | 150 | Red |
| 41020149F | 10 | 5 | 4 | 10 | 7 | 5 | 150 | Red |
| - | 1 | 5 | - | - | - | - | - | - |
| 41020174F | 10 | 8 | 6.4 | 16 | 11.2 | 8 | 240 | Blue |
| 41020193F | 2 | 10 | 8 | 20 | 14 | 10 | 300 | Orange |
| 41020024F | 6 | 10 | 8 | 20 | 14 | 10 | 300 | Orange |
| 41020018F | 10 | 10 | 8 | 20 | 14 | 10 | 300 | Orange |
| 41020199F | 3 | 12 | 9.6 | 24 | 16.8 | 12 | 300 | Orange |
| 41020202F | 4 | 12 | 9.6 | 24 | 16.8 | 12 | 300 | Orange |
| 41020204F | 5 | 12 | 9.6 | 24 | 16.8 | 12 | 300 | Orange |

Webbing slings 0,5 - 12 t

Technical data

| Part code | EWL | WLL ton | Choke Hitch ton | Basket Hitch 0° ton | Basket Hitch 0-45° ton | Basket Hitch 45°-60° ton | Webbing width mm | Colour |
|-----------|-----|------------|--------------------|------------------------|---------------------------|-----------------------------|---------------------|--------|
| 41020064F | 6 | 12 | 9.6 | 24 | 16.8 | 12 | 300 | Orange |
| 41020206F | 8 | 12 | 9.6 | 24 | 16.8 | 12 | 300 | Orange |
| 41020207F | 10 | 12 | 9.6 | 24 | 16.8 | 12 | 300 | Orange |