

## Endless webbing slings FORANKRA 0,5 - 10 t

---

### Product information



Single-layered endless webbing slings are also available with a double layer, which doubles the workload capacity for the same sling width.

Color coded.

... [Read more](#)

---

**Material:** Polyester

**Temperature range:** -40°C up to 100°C

**Note:** Standard dimensional tolerance is  $\pm 3\%$ . Lengths can vary within the tolerance range!.

## Endless webbing slings FORANKRA 0,5 - 10 t

### Technical data

EWL m	WLL ton	Band width mm	Colour
1	1	30	Purple
1.5	1	30	Purple
2	1	30	Purple
3	1	30	Purple
4	1	30	Purple
5	1	30	Purple
6	1	30	Purple
8	1	30	Purple
10	1	30	Purple
1	2	60	Green
1.5	2	60	Green
2	2	60	Green
2.5	2	60	Green
3	2	60	Green
3.5	2	60	Green
4	2	60	Green
5	2	60	Green
6	2	60	Green
8	2	60	Green
10	2	60	Green
1	3	90	Yellow
1.5	3	90	Yellow
2	3	90	Yellow
2.5	3	90	Yellow
3	3	90	Yellow
4	3	90	Yellow
5	3	90	Yellow
6	3	90	Yellow
8	3	90	Yellow
10	3	90	Yellow
1	4	120	Grey

## Endless webbing slings FORANKRA 0,5 - 10 t

### Technical data

EWL m	WLL ton	Band width mm	Colour
2	4	120	Grey
3	4	120	Grey
4	4	120	Grey
5	4	120	Grey
6	4	120	Grey
8	4	120	Grey
10	4	120	Grey
1	5	150	Red
2	5	150	Red
3	5	150	Red
4	5	150	Red
5	5	150	Red
6	5	150	Red
8	5	150	Red
10	5	150	Red
2	6	180	Brown
3	6	180	Brown
4	6	180	Brown
5	6	180	Brown
6	6	180	Brown
8	6	180	Brown
10	6	180	Brown
2	8	240	Blue
3	8	240	Blue
4	8	240	Blue
5	8	240	Blue
6	8	240	Blue
8	8	240	Blue
10	8	240	Blue
4	10	300	Orange
5	10	300	Orange

## Endless webbing slings FORANKRA 0,5 - 10 t

### Technical data

EWL m	WLL ton	Band width mm	Colour
6	10	300	Orange
8	10	300	Orange
10	10	300	Orange