


## Wire rope 6x19-WSC class A

### Product information



The 6x19 steel wire rope is specially designed to meet the demands of mountain applications and wall protection.

Thanks to its Class A galvanization, this wire rope offers superior corrosion resistance compared to Class B galvanized wire ropes, ensuring increased durability even in the most extreme conditions.

#### Features:

- **Class A Galvanization:** Class A galvanization provides optimal protection against corrosion, extending the wire rope's lifespan and reducing maintenance needs.
- **Static Use:** These wire ropes are non-greased, making them ideal for generally static applications where mobility is not required, thus offering maximum safety for wall protection installations.
- **Applications:** Perfectly suited for mountain environments, this wire rope is ideal for wall protection, securing high-risk areas, and fixed installations <sup>at altitude</sup> ... [Read more](#)

**Rope construction:** 6x19-WSC

**Marking:** According to standard

**Standard:** EN 12385-4

**RCN:** 4

## Wire rope 6x19-WSC class A

### Technical data

Part code	Rope diameter mm	Tensile strength N/mm <sup>2</sup>	Finish	Rope lay	Min. breaking force kN	Lubrication	Weight kg/100m
101101204251000	12	1,770	Galvanized	sZ	92.3	Dry	55
101101604251000	16	1,770	Galvanized	sZ	164	Dry	97.5
101102004251000	20	1,770	Galvanized	sZ	256	Dry	165
101102204251000	22	1,770	Galvanized	sZ	304	Dry	195