



Gantry Crane PRC

Product information

Standard Equipment:

- Dismountable gantry in 3 elements for indoor or outdoor use
- 4 swivel polyamide wheels
- Welded construction (welders certified NF EN ISO 9606-1: 2017)
- Rolling gantry under load on smooth ground or clean slab
- Hoist speed limited to 16 m/min for lifting and 10 m/min for direction
- Very easy gantry movement / easy empty movement
- Packaging on pallets and shrink wrap film

Optional Equipment:

- Swivel polyamide wheels equipped with brakes
- Lockable switch
- Cable reel
- Power supply line
- Dimensions adapted on request
- Specific treatment (GALVANIZATION, etc.)
- Calculation note

Manufactured in accordance with the Machinery Directive 2006/42/EC

Marking: WLL, EC, Serial number, year of manufacture

Temperature range: From -10° up to +40°

Finish: Yellow Rust-proof paint (RAL 1028)

Note: Can be moved while loaded on flat, smooth and clean surfaces

Warning: Do not pull with a motorised device

WLL ton	IPE	Beam length m	B,	M mm	N mm	L
0.5	180	2.5	150	2,650	1,780	2,500
0.5	180	3	150	3,150	2,280	3,000
0.5	180	3.5	150	3,650	2,780	3,500
0.5	180	4	150	4,150	3,280	4,000
0.5	180	4.5	150	4,650	3,780	4,500
0.5	180	5	150	5,150	4,280	5,000
1	200	2.5	200	2,650	1,780	2,500
1	200	3	200	3,150	2,280	3,000
1	200	3.5	200	3,650	2,780	3,500
1	200	4	200	4,150	3,280	4,000
1	220	4.5	200	4,650	3,780	4,500
1	220	5	200	5,150	4,280	5,000
1.6	200	2.5	200	2,680	1,750	2,500
1.6	200	3	200	3,180	2,250	3,000
3.2	270	3	250	3,230	2,200	3,000
3.2	270	3.5	250	3,730	2,700	3,500

Technical data



Blueprint

