Lifting Solutions Group
Axel Johnson International

Gantry Crane TDL

Product information



Standard Equipment:

- Dismountable gantry in 3 elements - lightweight construction
- 4 swivel polyamide wheels
- Welded construction (welders certified NF EN ISO 9606-1: 2017)
- Hoist speed limited to 6 m/min
- Advantage of reduced transport packaging
- Very easy gantry movement / easy empty movement
- Packaging on pallets and shrink-wrapped film

Optional Equipment:

- Swivel polyamide wheels equipped with brakes
- Lockable switch
- Cable reel
- Power supply line
- Dimensions adapted on request

Manufactured in accordance with the Machinery Directive 2006/42/EC ... *Read more*

Marking: WLL, EC, Serial number, year of manufacture
Temperature range: From -10° up to +40°
Finish: Yellow Rust-proof paint (RAL 1028)
Warning: This gantry crane must not be moved under load. Do not pull with a motorised device.

Traction Levage
marketingtl@traclev.com
© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Gantry Crane TDL

Blueprint



Technical data

WLL ton	IPE	Beam length m	A mm	B mm	L mm
0.5	120	2.5	40	125	2,500
0.5	120	3	40	125	3,000
0.5	160	4	40	125	4,000
0.5	160	5	40	125	5,000
1	140	2.5	40	125	2,500
1	160	3	40	125	3,000
1	180	4	40	125	4,000
1	200	5	40	125	5,000
1.6	180	2.5	40	125	2,500
1.6	200	3	40	125	3,000
1.6	220	4	40	125	4,000
1.6	270	5	40	125	5,000
2	200	2.5	40	125	2,500
2	220	3	40	125	3,000
2	240	4	40	125	4,000
2	240	5	40	125	5,000
3.2	220	2.5	50	200	2,500
3.2	240	3	50	200	3,000
3.2	270	4	50	200	4,000
3.2	300	5	50	200	5,000

Traction Levage
marketingtl@traclev.com
© November 2026 - All Rights Reserved