Lifting Solutions Group
Axel Johnson International

Gantry Crane TDT

Product information

Standard Equipment:

- Dismountable gantry in 3 elements
- Welded construction (welders certified NF EN ISO 9606-1: 2017)
- 4 swivel polyamide wheels
- Hoist speed limited to 6 m/min
- Advantage of reduced transport packaging
- Very easy gantry movement / easy empty movement
- Packaging on pallets and shrink-wrapped film

Optional Equipment:

- Swivel polyamide wheels equipped with brakes
- Lockable switch
- Cable reel
- Power supply line
- Dimensions adapted on request

Manufactured in accordance with the Machinery Directive 2006/42/EC ... *Read more*

Marking: WLL, EC, Serial number, year of manufacture
Temperature range: From -10° up to +40°
Finish: Yellow Rust-proof paint (RAL 1028)
Warning: This gantry crane must not be moved under load. Do not pull with a motorised device.

Traction Levage
marketingtl@traclev.com
© September 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Gantry Crane TDT

Blueprint



Technical data

WLL ton	IPE	Beam length m	A mm	B mm	C mm	L mm
1	140	2.5	40	125	70	2,500
1	160	3	40	125	70	3,000
1	180	4	40	125	70	4,000
1	200	5	40	125	70	5,000
2	200	2.5	40	125	70	2,500
2	220	3	40	125	70	3,000
2	240	4	40	125	70	4,000
2	240	5	40	125	70	5,000
3.2	220	2.5	50	200	70	2,500
3.2	240	3	50	200	70	3,000
3.2	270	4	50	200	70	4,000
3.2	300	5	50	200	70	5,000
5	270	2.5	65	250	90	2,500
5	300	3	65	250	90	3,000
5	330	4	65	250	90	4,000
5	360	5	65	250	90	5,000

Traction Levage
marketingtl@traclev.com

© September 2026 - All Rights Reserved