

Gantry Crane TDT

Product information

Standard Equipment:

- Dismountable gantry in 3 elements
- Welded construction (welders certified NF EN ISO 9606-1: 2017)
- 4 swivel polyamide wheels
- Hoist speed limited to 6 m/min
- Advantage of reduced transport packaging
- Very easy gantry movement / easy empty movement
- Packaging on pallets and shrink-wrapped film

Optional Equipment:

- Swivel polyamide wheels equipped with brakes
- Lockable switch
- Cable reel
- Power supply line
- · Dimensions adapted on request

Manufactured in accordance with the Machinery Directive 2006/42/EC

Marking: WLL, EC, Serial number, year of manufacture

Temperature range: From -10° up to +40° Finish: Yellow Rust-proof paint (RAL 1028)

Warning: This gantry crane must not be moved under load. Do not pull with a motorised device.

| WLL ton | IPE | Beam length m | A mm | B mm | C mm | L mm |
|------------|-----|------------------|------|------|------|---------|
| 1 | 140 | 2.5 | 40 | 125 | 70 | 2,500 |
| 1 | 160 | 3 | 40 | 125 | 70 | 3,000 |
| 1 | 180 | 4 | 40 | 125 | 70 | 4,000 |
| 1 | 200 | 5 | 40 | 125 | 70 | 5,000 |
| 2 | 200 | 2.5 | 40 | 125 | 70 | 2,500 |
| 2 | 220 | 3 | 40 | 125 | 70 | 3,000 |
| 2 | 240 | 4 | 40 | 125 | 70 | 4,000 |
| 2 | 240 | 5 | 40 | 125 | 70 | 5,000 |
| 3.2 | 220 | 2.5 | 50 | 200 | 70 | 2,500 |
| 3.2 | 240 | 3 | 50 | 200 | 70 | 3,000 |
| 3.2 | 270 | 4 | 50 | 200 | 70 | 4,000 |
| 3.2 | 300 | 5 | 50 | 200 | 70 | 5,000 |
| 5 | 270 | 2.5 | 65 | 250 | 90 | 2,500 |
| 5 | 300 | 3 | 65 | 250 | 90 | 3,000 |
| 5 | 330 | 4 | 65 | 250 | 90 | 4,000 |
| 5 | 360 | 5 | 65 | 250 | 90 | 5,000 |

Technical data

Blueprint

