

## Lifting Point 8-211 Long bolt

---

### Product information



- Rotates through 360° and pivot 90°
- Load rated parts are 100% magnaflux crack detected.
- Individual forged parts and cap screw are traceable to Test Certification.
- Bolts are Metric thread (ASME / ANSI B18.3.1M).
- Proof tested to 2.5 times the WLL.
- Fatigue rated to 1.5 times the WLL.
- Quick and simple assembly, just a tapped hole is required.

... [Read more](#)

---

**Features:** Built-in RFID/NFC chip

**Material:** Alloy steel, quenched and tempered


**Marking:** According to standard, CE-marked

**Standard:** EN 1677-1

**Safety factor:** 4:1

## Lifting Point 8-211 Long bolt

### Blueprint



### Technical data

| Part code       | WLL ton | Thread mm | Torque Nm | Pitch DIN13 | A mm | B mm | C mm | D mm | F mm | G mm | SW mm | J mm | K mm | L mm | N mm | E mm | M mm | Weight kg |
|-----------------|---------|-----------|-----------|-------------|------|------|------|------|------|------|-------|------|------|------|------|------|------|-----------|
| 42158211003105L | 0.3     | M 8       | 30        | 1.25        | 30   | 35   | 35   | 11   | 86   | 55   | 13    | 77   | 34   | 41   | 24   | 76   | M 8  | 0.4       |
| 42158211006125L | 0.63    | M 10      | 60        | 1.5         | 30   | 35   | 36   | 11   | 86   | 55   | 17    | 78   | 34   | 40   | 24   | 96   | M 10 | 0.4       |
| 42158211010150L | 1       | M 12      | 100       | 1.75        | 33   | 38   | 44   | 14   | 99   | 57   | 19    | 89   | 38   | 42   | 31   | 114  | M 12 | 0.5       |
| 42158211015185L | 1.5     | M 16      | 150       | 2           | 33   | 38   | 46   | 14   | 99   | 57   | 24    | 89   | 38   | 40   | 31   | 149  | M 16 | 0.7       |
| 42158211025230L | 2.5     | M 20      | 250       | 2.5         | 50   | 54   | 56   | 16   | 142  | 82   | 30    | 132  | 53   | 70   | 49   | 186  | M 20 | 1.7       |
| 42158211040265L | 4       | M 24      | 400       | 3           | 50   | 54   | 59   | 16   | 143  | 82   | 36    | 132  | 53   | 67   | 45   | 221  | M 24 | 2         |
| 42158211050340L | 5       | M 30      | 500       | 3.5         | 60   | 65   | 81   | 23   | 170  | 99   | 46    | 153  | 64   | 67   | 59   | 278  | M 30 | 2.9       |
| 42158211080300L | 8       | M 36      | 800       | 4           | 77   | 85   | 101  | 27   | 225  | 124  | 55    | 205  | 80   | 97   | 69   | 222  | M 36 | 6.9       |
| 42158211100350L | 10      | M 42      | 1,000     | 4.5         | 77   | 85   | 104  | 27   | 225  | 124  | 65    | 204  | 79   | 94   | 69   | 272  | M 42 | 7.9       |
| 42158211150350L | 15      | M 42      | 1,500     | 4.5         | 95   | 104  | 112  | 36   | 258  | 158  | 65    | 229  | 98   | 110  | 98   | 264  | M 42 | 13.5      |
| 42158211200385L | 20      | M 48      | 2,000     | 5           | 95   | 104  | 120  | 36   | 260  | 158  | 75    | 230  | 99   | 104  | 98   | 295  | M 48 | 15.5      |