


Electric Chain Hoist Elephant BETA

Product information



The Elephant Beta 230 VAC electric chain hoists are light weight, compact and ideal for light installation work.

Features

- Slip clutch for overload prevention
- Self-locking brake that will hold the load at any required height
- Very low own weight, only 7.5 kg.
- Very compact.
- In case of overload, the hooks will gradually bend and do not suddenly break off.
- Grade 10 load chain.

Technical specification:

- Insulation class B.
- FEM 9.511 motor: 1Am.
- Power supply 230VAC.
- Protection class IP54
- Control power supply 230VAC direct control.

Standard delivery

- 3 m lifting height (maximum distance between top and bottom hook).
- 1.8 m control cable, direct control.
- 3 m power cable.
- Chain bag max 10 m.
- Trolley not included.

Option


- Other hoisting and operating height is also possible

... [Read more](#)

Marking: CE-marked

Electric Chain Hoist Elephant BETA

Blueprint



Technical data

| Part code | WLL kg | Lifting height m | Lifting speed m/min | Number of falls | Model | Motor kW | Max. lifting height m | Duty rating % ED | Load chain mm | Construction height mm | Weight kg |
|-----------------|-----------|------------------------|---------------------------|--------------------|----------------|-------------|-----------------------------|---------------------|------------------|------------------------------|--------------|
| 540112501390224 | 125 | 3 | 6,5 | 1 | BETA-125KG-3M | 0.18 | 10 | 25 | 3 x 9 | 280 | 7.25 |
| 540112501390220 | 125 | - | 6,5 | 1 | BETA-H/125KG | 0.18 | 10 | 25 | 3 x 9 | 280 | 7.5 |
| 540105110014 | 125 | 4 | 6,5 | 1 | BETA-125KG-4M | 0.18 | 10 | 25 | 3 x 9 | 280 | 8.5 |
| 540112501390225 | 125 | 5 | 6,5 | 1 | BETA-125KG-5M | 0.18 | 10 | 25 | 3 x 9 | 280 | 9.75 |
| 540112501390226 | 125 | 6 | 6,5 | 1 | BETA-125KG-6M | 0.18 | 10 | 25 | 3 x 9 | 280 | 11 |
| 540105110017 | 125 | 7 | 6,5 | 1 | BETA-125KG-7M | 0.18 | 10 | 25 | 3 x 9 | 280 | 12.25 |
| 540112501390227 | 125 | 8 | 6,5 | 1 | BETA-125KG-8M | 0.18 | 10 | 25 | 3 x 9 | 280 | 13.5 |
| 540105110019 | 125 | 9 | 6,5 | 1 | BETA-125KG-9M | 0.18 | 10 | 25 | 3 x 9 | 280 | 14.75 |
| 540112501390228 | 125 | 10 | 6,5 | 1 | BETA-125KG-10M | 0.18 | 10 | 25 | 3 x 9 | 280 | 16 |
| 540120001220224 | 200 | 3 | 3,8 | 1 | BETA-200KG-3M | 0.18 | 10 | 25 | 3 x 9 | 280 | 7.25 |
| 540120001220220 | 200 | - | 3,8 | 1 | BETA-H/200KG | 0.18 | 10 | 25 | 3 x 9 | 280 | 7.5 |
| 540105110034 | 200 | 4 | 3,8 | 1 | BETA-200KG-4M | 0.18 | 10 | 25 | 3 x 9 | 280 | 8.5 |
| 540120001220225 | 200 | 5 | 3,8 | 1 | BETA-200KG-5M | 0.18 | 10 | 25 | 3 x 9 | 280 | 9.75 |
| 540120001220226 | 200 | 6 | 3,8 | 1 | BETA-200KG-6M | 0.18 | 10 | 25 | 3 x 9 | 280 | 11 |
| 540105110037 | 200 | 7 | 3,8 | 1 | BETA-200KG-7M | 0.18 | 10 | 25 | 3 x 9 | 280 | 12.25 |
| 540120001220227 | 200 | 8 | 3,8 | 1 | BETA-200KG-8M | 0.18 | 10 | 25 | 3 x 9 | 280 | 13.5 |
| 540105110039 | 200 | 9 | 3,8 | 1 | BETA-200KG-9M | 0.18 | 10 | 25 | 3 x 9 | 280 | 14.75 |
| 540120001220228 | 200 | 10 | 3,8 | 1 | BETA-200KG-10M | 0.18 | 10 | 25 | 3 x 9 | 280 | 16 |