Lifting Solutions Group
Axel Johnson International

Electric Chain Hoist Elephant BETA

Product information



The Elephant Beta 230 VAC electric chain hoists are light weight, compact and ideal for light installation work.

Features

- Slip clutch for overload prevention
- Self-locking brake that will hold the load at any required height
- Very low own weight, only 7.5 kg.
- Very compact.
- In case of overload, the hooks will gradually bend and do not suddenly break off.
- Grade 10 load chain.

Technical specification:

- Insulation class B.
- FEM 9.511 motor: 1Am.
- Power supply 230VAC.
- Protection class IP54
- Control power supply 230VAC direct control.

Standard delivery

- 3 m lifting height (maximum distance between top and bottom hook).
- 1.8 m control cable, direct control.
- 3 m power cable.
- Chain bag max 10 m.
- Trolley not included.

Option

- Other hoisting and operating height is also possible

... Read more

Marking: CE-mark


Traction Levage
marketingtl@traclev.com

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Electric Chain Hoist Elephant BETA

Blueprint



Technical data

Part code	WLL kg	Lifting height m	Lifting speed m/min	Number of falls	Model	Motor kW	Max. lifting height m	Duty rating % ED	Load chain mm	Construction height mm	Weight kg
540112501390224	125	3	6,5	1	BETA-125KG-3M	0.18	10	25	3 x 9	280	7.25
540112501390220	125	-	6,5	1	BETA-H/125KG	0.18	10	25	3 x 9	280	7.5
540105110014	125	4	6,5	1	BETA-125KG-4M	0.18	10	25	3 x 9	280	8.5
540112501390225	125	5	6,5	1	BETA-125KG-5M	0.18	10	25	3 x 9	280	9.75
540112501390226	125	6	6,5	1	BETA-125KG-6M	0.18	10	25	3 x 9	280	11
540105110017	125	7	6,5	1	BETA-125KG-7M	0.18	10	25	3 x 9	280	12.25
540112501390227	125	8	6,5	1	BETA-125KG-8M	0.18	10	25	3 x 9	280	13.5
540105110019	125	9	6,5	1	BETA-125KG-9M	0.18	10	25	3 x 9	280	14.75
540112501390228	125	10	6,5	1	BETA-125KG-10M	0.18	10	25	3 x 9	280	16
540120001220224	200	3	3,8	1	BETA-200KG-3M	0.18	10	25	3 x 9	280	7.25
540120001220220	200	-	3,8	1	BETA-H/200KG	0.18	10	25	3 x 9	280	7.5
540105110034	200	4	3,8	1	BETA-200KG-4M	0.18	10	25	3 x 9	280	8.5
540120001220225	200	5	3,8	1	BETA-200KG-5M	0.18	10	25	3 x 9	280	9.75
540120001220226	200	6	3,8	1	BETA-200KG-6M	0.18	10	25	3 x 9	280	11
540105110037	200	7	3,8	1	BETA-200KG-7M	0.18	10	25	3 x 9	280	12.25
540120001220227	200	8	3,8	1	BETA-200KG-8M	0.18	10	25	3 x 9	280	13.5
540105110039	200	9	3,8	1	BETA-200KG-9M	0.18	10	25	3 x 9	280	14.75
540120001220228	200	10	3,8	1	BETA-200KG-10M	0.18	10	25	3 x 9	280	16

© November 2026 - All Rights Reserved