



Electric Chain Hoist Elephant FBH 400 V 2 speed

Product information



The 400 V electric chain hoists are extremely solid and have a robust sheet steel housing. Very popular as it is ready to use with limit switches, 24 V control voltage, control unit and plug connections. The high duty cycle and high lifting speed ensure trouble-free operation and a long service life.

Properties

- Slip clutch against overload.
- Brake that holds the load at any desired height.
- Limit switches for highest and lowest hook positions.
- Operation 24 Volt control voltage.
- Power and control cables are equipped with plug connection.
- Phase protection against incorrect rotation of the motor.
- Galvanized load chain, Class DAT (Grade 8).
- Operating voltage 400 VAC / 50 Hz.
- In case of overload, the hooks will gradually bend and do not suddenly break off.
- 2 speed.

Standard delivery

- 3 m lifting height (maximum distance between top and bottom hook).
- 1.8 m control cable.
- Limit switches highest and lowest hook position.
- Push-button 24 V control unit.
- 4 m power cable.
- Plastic chain bucket for 3 m lifting height.
- Trolley not included.

Option

- Increased lifting and/or control height.
- Larger chain bucket > 3 m lifting height.
- Radio remote control.
- Push / electric trolley.
- 440 V / 60 Hz on request

Marking: According to standard, CE-marked

Standard: EN 12100, EN 14492, EN 818-7

Part code	WLL ton	Lifting height m	Lifting speed m/min	Number of falls	Model	Operation voltage (V)	Motor kW	Max. lifting height m	Protection	Duty rating % ED	Duty group of hoist FEM 9.511	Load chain mm	Construction height mm	A mm	B mm	C mm	D mm	H mm	K mm	L mm	M mm	N mm	O mm	Isolation class	Weight kg
0512001-3	0.5	3	7/1,8	1	FBH/500KG/3M	400	0.9/0.25	30	IP54	40/20	1AM	6.3 x 19.1	480	161	124	224	311	480	36	26	86	24	19	E	43
0512001-4	0.5	4	7/1,8	1	FBH/500KG/4M	400	0.9/0.25	30	IP54	40/20	1AM	6.3 x 19.1	480	161	124	224	311	480	36	26	86	24	19	E	45
0512001-5	0.5	5	7/1,8	1	FBH/500KG/5M	400	0.9/0.25	30	IP54	40/20	1AM	6.3 x 19.1	480	161	124	224	311	480	36	26	86	24	19	E	47
0512001-6	0.5	6	7/1,8	1	FBH/500KG/6M	400	0.9/0.25	30	IP54	40/20	1AM	6.3 x 19.1	480	161	124	224	311	480	36	26	86	24	19	E	49
0512001-7	0.5	7	7/1,8	1	FBH/500KG/7M	400	0.9/0.25	30	IP54	40/20	1AM	6.3 x 19.1	480	161	124	224	311	480	36	26	86	24	19	E	51
0512001-8	0.5	8	7/1,8	1	FBH/500KG/8M	400	0.9/0.25	30	IP54	40/20	1AM	6.3 x 19.1	480	161	124	224	311	480	36	26	86	24	19	E	52
0512001-9	0.5	9	7/1,8	1	FBH/500KG/9M	400	0.9/0.25	30	IP54	40/20	1AM	6.3 x 19.1	480	161	124	224	311	480	36	26	86	24	19	E	54
0512001-10	0.5	10	7/1,8	1	FBH/500KG/10M	400	0.9/0.25	30	IP54	40/20	1AM	6.3 x 19.1	480	161	124	224	311	480	36	26	86	24	19	E	56
0512003-3	1	3	7,6/1,9	1	FBH/1000KG/3M	400	1.6/0.4	30	IP54	40/20	1Am	7.1 x 21.2	570	170	128	239	348	570	43	33	107	31	23	E	58
0512003-4	1	4	7,6/1,9	1	FBH/1000KG/4M	400	1.6/0.4	30	IP54	40/20	1Am	7.1 x 21.2	570	170	128	239	348	570	43	33	107	31	23	E	60
0512003-5	1	5	7,6/1,9	1	FBH/1000KG/5M	400	1.6/0.4	30	IP54	40/20	1Am	7.1 x 21.2	570	170	128	239	348	570	43	33	107	31	23	E	62
0512003-6	1	6	7,6/1,9	1	FBH/1000KG/6M	400	1.6/0.4	30	IP54	40/20	1Am	7.1 x 21.2	570	170	128	239	348	570	43	33	107	31	23	E	63
0512003-7	1	7	7,6/1,9	1	FBH/1000KG/7M	400	1.6/0.4	30	IP54	40/20	1Am	7.1 x 21.2	570	170	128	239	348	570	43	33	107	31	23	E	64
0512003-8	1	8	7,6/1,9	1	FBH/1000KG/8M	400	1.6/0.4	30	IP54	40/20	1Am	7.1 x 21.2	570	170	128	239	348	570	43	33	107	31	23	E	66
0512003-9	1	9	7,6/1,9	1	FBH/1000KG/9M	400	1.6/0.4	30	IP54	40/20	1Am	7.1 x 21.2	570	170	128	239	348	570	43	33	107	31	23	E	68

0512003-10	1	10	7,6/1,9	1	FBH/1000KG/10M	400	1.6/0.4	30	IP54	40/20	1Am	7.1 x 21.2	570	170	128	239	348	570	43	33	107	31	23	E	70
0512005-10	1	10	3,8/1	2	FBH/2000KG/10M	400	1.6/0.4	15	IP54	40/20	1Am	7.1 x 21.2	710	133	165	239	372	710	53	42	144	44	30	E	79
0512005-3	2	3	3,8/1	2	FBH/2000KG/3M	400	1.6/0.4	15	IP54	40/20	1Am	7.1 x 21.2	710	133	165	239	372	710	53	42	144	44	30	E	64
0512005-4	2	4	3,8/1	2	FBH/2000KG/4M	400	1.6/0.4	15	IP54	40/20	1Am	7.1 x 21.2	710	133	165	239	372	710	53	42	144	44	30	E	66
0512005-5	2	5	3,8/1	2	FBH/2000KG/5M	400	1.6/0.4	15	IP54	40/20	1Am	7.1 x 21.2	710	133	165	239	372	710	53	42	144	44	30	E	68
0512005-6	2	6	3,8/1	2	FBH/2000KG/6M	400	1.6/0.4	15	IP54	40/20	1Am	7.1 x 21.2	710	133	165	239	372	710	53	42	144	44	30	E	70
0512005-7	2	7	3,8/1	2	FBH/2000KG/7M	400	1.6/0.4	15	IP54	40/20	1Am	7.1 x 21.2	710	133	165	239	372	710	53	42	144	44	30	E	73
0512005-8	2	8	3,8/1	2	FBH/2000KG/8M	400	1.6/0.4	15	IP54	40/20	1Am	7.1 x 21.2	710	133	165	239	372	710	53	42	144	44	30	E	75
0512005-9	2	9	3,8/1	2	FBH/2000KG/9M	400	1.6/0.4	15	IP54	40/20	1Am	7.1 x 21.2	710	133	165	239	372	710	53	42	144	44	30	E	77
0512007-10	2	10	2,5/0,6	3	FBH/3000KG/10M	400	1.6/0.4	10	IP54	40/20	1Am	7.1 x 21.2	810	148	208	239	427	810	60	50	165	49	35	E	106
0512007-3	3	3	2,5/0,6	3	FBH/3000KG/3M	400	1.6/0.4	10	IP54	40/20	1Am	7.1 x 21.2	810	148	208	239	427	810	60	50	165	49	35	E	78
0512007-4	3	4	2,5/0,6	3	FBH/3000KG/4M	400	1.6/0.4	10	IP54	40/20	1Am	7.1 x 21.2	810	148	208	239	427	810	60	50	165	49	35	E	82
0512007-5	3	5	2,5/0,6	3	FBH/3000KG/5M	400	1.6/0.4	10	IP54	40/20	1Am	7.1 x 21.2	810	148	208	239	427	810	60	50	165	49	35	E	86
0512007-6	3	6	2,5/0,6	3	FBH/3000KG/6M	400	1.6/0.4	10	IP54	40/20	1Am	7.1 x 21.2	810	148	208	239	427	810	60	50	165	49	35	E	90
0512007-7	3	7	2,5/0,6	3	FBH/3000KG/7M	400	1.6/0.4	10	IP54	40/20	1Am	7.1 x 21.2	810	148	208	239	427	810	60	50	165	49	35	E	94
0512007-8	3	8	2,5/0,6	3	FBH/3000KG/8M	400	1.6/0.4	10	IP54	40/20	1Am	7.1 x 21.2	810	148	208	239	427	810	60	50	165	49	35	E	98
0512007-9	3	9	2,5/0,6	3	FBH/3000KG/9M	400	1.6/0.4	10	IP54	40/20	1Am	7.1 x 21.2	810	148	208	239	427	810	60	50	165	49	35	E	102

Blueprint

