

Electric Chain Hoist Elephant Alpha ALHVDH 230V

Product information



The ALHVDH 230 V electric chain hoist is a compact chain hoist.

The ALHVDH has a very low own weight (aluminum house). Can be used in many applications due to the high duty cycle in combination with a high lifting speed.

Features

- Operation at the lower hook.
- Variable speed adjustable by turning the handle.
- Spiral control cable around the load chain.
- · Slip clutch against overload.
- Self locking brake that holds the load at any desired height.
- In case of overload, the hooks will gradually bend and do not suddenly break off.
- Galvanized load chain, class DAT (Grade 8).

Technical specification:

- · Insulation class B.
- FEM 9.511 motor: 1Am.
- Power supply 230VAC.
- Protection class IP54.

Standard delivery

- 2,5 m lifting height (max distance between top and lower hook).
- 4 m power cable.
- Plastic chain container for 3 m lifting height.
- Trolley not included.

Option

· Push trolley.

| Part code | WLL ton | Lifting height m | Lifting speed m/min | Number of falls | Model | Motor kW | Duty rating % ED | Load chain mm | Construction height mm | Weight kg |
|-----------|------------|---------------------|------------------------|-----------------|------------|-------------|------------------|------------------|------------------------|--------------|
| 0513205 | 0.25 | 2.5 | 0,9-10 | 1 | ALHVDH/250 | 0.6 | 25 | 4.0 x 12 | 673 | 22 |

Blueprint

