



## Chain Hoist Elephant HOISTMAN

### Product information



The Elephant HOISTMAN is a lightweight mini-hand chain hoist. Very compact for use in confined spaces and where a low self weight is desirable.

#### Features

- Steel chromed body.
- Little operating effort at maximum load due to bearing shafts.
- Double pawl system.
- Self-locking brake that holds the load at any desired height.
- Top and bottom hook have safety latches.
- In case of overload, the hooks will gradually bend and do not suddenly break off.
- Galvanized load chain (Grade 10).
- Galvanized hand chain

#### Standard delivery

- 2,5 meters lifting height (maximum distance between top and bottom hook).
- 2 meters operating height.

**Marking:** According to standard, CE-marked

**Standard:** EN 13157, EN 818-7

Part code	WLL ton	Lifting height m	Number of falls	Model	Load chain mm	Hand chain mm	Construction height mm	Hand force max. kg	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	I mm	Weight kg
0100000	0.15	2.5	1	HOISTMAN-150KG	3.1 X 9.3	2.5 X 14	220	17	220	103	46	57	102	14	24	11	9	2.8
500500020400310	0.15	4	1	HOISTMAN-150KG	3.1 X 9.3	2.5 X 14	220	17	220	103	46	57	102	14	24	11	9	3.5
500500020500310	0.15	5	1	HOISTMAN-150KG	3.1 X 9.3	2.5 X 14	220	17	220	103	46	57	102	14	24	11	9	4
500500020600310	0.15	6	1	HOISTMAN-150KG	3.1 X 9.3	2.5 X 14	220	17	220	103	46	57	102	14	24	11	9	4.5
500500020700310	0.15	7	1	HOISTMAN-150KG	3.1 X 9.3	2.5 X 14	220	17	220	103	46	57	102	14	24	11	9	5
500500020800310	0.15	8	1	HOISTMAN-150KG	3.1 X 9.3	2.5 X 14	220	17	220	103	46	57	102	14	24	11	9	5.5
500500020900310	0.15	9	1	HOISTMAN-150KG	3.1 X 9.3	2.5 X 14	220	17	220	103	46	57	102	14	24	11	9	6
500500021000310	0.15	10	1	HOISTMAN-150KG	3.1 X 9.3	2.5 X 14	220	17	220	103	46	57	102	14	24	11	9	6.5
0100002	0.25	2.5	1	HOISTMAN-250KG	3.1 X 9.3	2.5 X 14	220	20	220	103	46	57	102	14	24	11	9	2.8
500500030400310	0.25	4	1	HOISTMAN-250KG	3.1 X 9.3	2.5 X 14	220	20	220	103	46	57	102	14	24	11	9	3.5
500500030500310	0.25	5	1	HOISTMAN-250KG	3.1 X 9.3	2.5 X 14	220	20	220	103	46	57	102	14	24	11	9	4
500500030600310	0.25	6	1	HOISTMAN-250KG	3.1 X 9.3	2.5 X 14	220	20	220	103	46	57	102	14	24	11	9	4.5
500500030700310	0.25	7	1	HOISTMAN-250KG	3.1 X 9.3	2.5 X 14	220	20	220	103	46	57	102	14	24	11	9	5
500500030800310	0.25	8	1	HOISTMAN-250KG	3.1 X 9.3	2.5 X 14	220	20	220	103	46	57	102	14	24	11	9	5.5
500500030900310	0.25	9	1	HOISTMAN-250KG	3.1 X 9.3	2.5 X 14	220	20	220	103	46	57	102	14	24	11	9	6
500500031000310	0.25	10	1	HOISTMAN-250KG	3.1 X 9.3	2.5 X 14	220	20	220	103	46	57	102	14	24	11	9	6.5

# Blueprint

