

Round Sling Powertex PRS

Product information



POWERTEX

Powertex Round slings PRS are made from high strength polyester yarn having a strong protective cover.

The PRS slings are color coded for quick and easy identification of the Working Load Limit (WLL).

Only standard slings with full ton WLL are shown in the chart, but PRS slings can be delivered with any WLL and length on request.

- Safe – All Powertex PRS slings are made from high strength industrial polyester and tested in accordance to EN 1492-2
- Durable protective cover
- Each sling carry a blue label giving correct WLL for different load connection methods and angles
- Each sling is marked with a unique serial number for safe sling registration
- Serial number is expressed both in numeric format as well as Barcode for quick registration and maintenance
- Year/Month calendar printed on the label where next inspection date can be marked or punched
- Printing on the blue label is protected by an additional transparent plastic layer for long life
- All roundslings carry a white label showing pictogram with important user warning instructions
- QR code for on-site access to Multilanguage user manuals
- Test certificate and Declaration of Conformity enclosed with each sling

Chemical resistance: Resistant to most acids, but not strong alkalis: ... [Read more](#)

Material: Polyester

Marking: According to standard, CE-marked, UKCA-marked, Powertex, WLL, EWL, manufacturing year, batch number, sling's unique serial number, QR code, Inspection calendar, user warning instructions

Temperature range: -40°C up to +100°C.


Standard: EN 1492-2

Note: According to EN 1492-2:2000+A1:2008: D.3.6: Slings should be protected from edges, friction and abrasion, whether from the load or the lifting appliance. Where reinforcements and protection against damage from edges and/or abrasion is supplied as part of the sling, this should be correctly positioned. It may be necessary to supplement this with additional protection.

Safety factor: 7:1

Round Sling Powertex PRS

Blueprint



Technical data

Part code	WLL ton
340100100050150	1
340100100080150	1
340100100100150	1
340100100150150	1
340100100200150	1
340100100250150	1
340100100300150	1
340100100400150	1
340100100500150	1
340100100600150	1
340100200050150	2
340100200100150	2
340100200150150	2
340100200200150	2
340100200250150	2
340100200300150	2
340100200400150	2
340100200500150	2
340100200600150	2
340100300050150	3
340100300100150	3
340100300150150	3

Round Sling Powertex PRS

Technical data

Part code	WLL ton
340100300200150	3
340100300250150	3
340100300300150	3
340100300400150	3
340100300500150	3
340100300600150	3
340100400100150	4
340100400150150	4
340100400200150	4
340100400300150	4
340100400400150	4
340100400500150	4
340100400600150	4
340100500050150	5
340100500100150	5
340100500150150	5
340100500200150	5
340100500250150	5
340100500300150	5
340100500400150	5
340100500500150	5
340100500600150	5
340100600200150	6
340100600300150	6
340100600400150	6
340100600500150	6
340100600600150	6
340100800100150	8
340100800200150	8
340100800300150	8
340100800400150	8

Round Sling Powertex PRS

Technical data

Part code	WLL ton
340100800500150	8
340100800600150	8
340101000200150	10
340101000300150	10
340101000400150	10
340101000500150	10
340101000600150	10
340101500200150	15
340101500300150	15
340101500400150	15
340101500500150	15
340101500600150	15
340101500800150	15
340101501000150	15
340102000200150	20
340102000300150	20
340102000400150	20
340102000500150	20
340102000600150	20
340102000800150	20
340102001000150	20
340103000200150	30
340103000300150	30
340103000400150	30
340103000500150	30
340103000600150	30
340103000800150	30
340103001000150	30