

Round slings assemblies 2-legs

Product information



Lighter alternative to a chain combination in, for example, transformer lifting without risk of insulator damage etc. Also available with self-locking hooks, rotating swivel hooks, shackles etc.

... [Read more](#)

Features: RFID-ready

Material: 100% polyester

Marking: CE-marked

Temperature range: -40°C - +100 °C

Safety factor: 4:1

Round slings assemblies 2-legs

Technical data

Part code	WLL ton	WLL 0-45° t	WLL 45-60° t	Length m
3403	1.4	1.4	1.0	1
3403	1.4	1.4	1.0	1.5
3403	1.4	1.4	1.0	2
3403	1.4	1.4	1.0	2.5
3403	1.4	1.4	1.0	3
3403	1.4	1.4	1.0	4
3403	2.8	2.8	2.0	1
3403	2.8	2.8	2.0	1.5
3403	2.8	2.8	2.0	2
3403	2.8	2.8	2.0	2.5
3403	2.8	2.8	2.0	3
3403	2.8	2.8	2.0	4
3403	4.2	4.2	3.0	1
3403	4.2	4.2	3.0	1.5
3403	4.2	4.2	3.0	2
3403	4.2	4.2	3.0	2.5
3403	4.2	4.2	3.0	3
3403	4.2	4.2	3.0	4
3403	7	7	5.0	1
3403	7	7	5.0	1.5
3403	7	7	5.0	2
3403	7	7	5.0	2.5
3403	7	7	5.0	3
3403	7	7	5.0	4
3403	11.2	11.2	8.0	2
3403	11.2	11.2	8.0	2.5
3403	11.2	11.2	8.0	3
3403	11.2	11.2	8.0	4
3403	11.2	11.2	8.0	5
3403	11.2	11.2	8.0	6