



## Round slings assemblies 2-legs

### Product information

Lighter alternative to a chain combination in, for example, transformer lifting without risk of insulator damage etc. Also available with self-locking hooks, rotating swivel hooks, shackles etc.

**Features:** RFID-ready

**Material:** 100% polyester

**Marking:** CE-marked

**Temperature range:** -40°C - +100 °C

**Safety factor:** 4:1

Part code	WLL ton	WLL 0-45° t	WLL 45-60° t	Length m
3403	1.4	1.4	1.0	1
3403	1.4	1.4	1.0	1.5
3403	1.4	1.4	1.0	2
3403	1.4	1.4	1.0	2.5
3403	1.4	1.4	1.0	3
3403	1.4	1.4	1.0	4
3403	2.8	2.8	2.0	1
3403	2.8	2.8	2.0	1.5

3403	2.8	2.8	2,0	2
3403	2.8	2.8	2,0	2.5
3403	2.8	2.8	2,0	3
3403	2.8	2.8	2,0	4
3403	4.2	4.2	3,0	1
3403	4.2	4.2	3,0	1.5
3403	4.2	4.2	3,0	2
3403	4.2	4.2	3,0	2.5
3403	4.2	4.2	3,0	3
3403	4.2	4.2	3,0	4
3403	7	7	5,0	1
3403	7	7	5,0	1.5
3403	7	7	5,0	2
3403	7	7	5,0	2.5
3403	7	7	5,0	3
3403	7	7	5,0	4
3403	11.2	11.2	8,0	2
3403	11.2	11.2	8,0	2.5
3403	11.2	11.2	8,0	3
3403	11.2	11.2	8,0	4
3403	11.2	11.2	8,0	5
3403	11.2	11.2	8,0	6