



Round slings assemblies 4-legs

Product information

Lighter alternative to a chain combination in, for example, transformer lifting without risk of insulator damage etc. Also available with self-locking hooks, rotating swivel hooks, shackles etc.

Features: RFID-ready

Material: 100% polyester

Marking: CE-marked

Temperature range: -40°C - +100 °C

Safety factor: 4:1

| Part code | WLL ton | WLL 0-45° t | WLL 45-60° t | Length m |
|-----------|---------|-------------|--------------|----------|
| 3403 | 2.1 | 2.1 | 1.5 | 1 |
| 3403 | 2.1 | 2.1 | 1.5 | 1.5 |
| 3403 | 2.1 | 2.1 | 1.5 | 2 |
| 3403 | 2.1 | 2.1 | 1.5 | 2.5 |
| 3403 | 2.1 | 2.1 | 1.5 | 3 |
| 3403 | 2.1 | 2.1 | 1.5 | 4 |
| 3403 | 4.2 | 4.2 | 3.0 | 1 |
| 3403 | 4.2 | 4.2 | 3.0 | 1.5 |

| | | | | |
|------|------|------|------|-----|
| 3403 | 4.2 | 4.2 | 3,0 | 2 |
| 3403 | 4.2 | 4.2 | 3,0 | 2.5 |
| 3403 | 4.2 | 4.2 | 3,0 | 3 |
| 3403 | 4.2 | 4.2 | 3,0 | 4 |
| 3403 | 6.3 | 6.3 | 4,5 | 1 |
| 3403 | 6.3 | 6.3 | 4,5 | 1.5 |
| 3403 | 6.3 | 6.3 | 4,5 | 2 |
| 3403 | 6.3 | 6.3 | 4,5 | 2.5 |
| 3403 | 6.3 | 6.3 | 4,5 | 3 |
| 3403 | 6.3 | 6.3 | 4,5 | 4 |
| 3403 | 10.5 | 10.5 | 7,5 | 1 |
| 3403 | 10.5 | 10.5 | 7,5 | 1.5 |
| 3403 | 10.5 | 10.5 | 7,5 | 2 |
| 3403 | 10.5 | 10.5 | 7,5 | 2.5 |
| 3403 | 10.5 | 10.5 | 7,5 | 3 |
| 3403 | 10.5 | 10.5 | 7,5 | 4 |
| 3403 | 17 | 17 | 11,8 | 2 |
| 3403 | 17 | 17 | 11,8 | 2.5 |
| 3403 | 17 | 17 | 11,8 | 3 |
| 3403 | 17 | 17 | 11,8 | 4 |
| 3403 | 17 | 17 | 11,8 | 5 |
| 3403 | 17 | 17 | 11,8 | 6 |