



## Load Ring RUD VRBG-FIX - on Plate for Bolting

### Product information

Load Ring on plate for bolting.











- Split force introduction thanks to multiple point fixing.
- Suspension ring can be pivoted through 180°.
- WLL possible up to 90° in load ring plane.
- Clear indication of the minimum WLL for all loading directions.

**Temperature range:** -20°C up to 100°C

**Safety factor:** 4:1

Part code	Code	WLL ton	A,	B,	C,	D,	E,	F,	K,	L	M mm	T mm	Weight kg
42157910387	VRBG-31.5t	31.5	180	42	42	130	75	120	46	400	195	265	66.35
42157910591	VRBG-FIX-31.5t	31.5	180	42	42	130	75	120	46	400	195	288	66.35
42157909951	VRBG-FIX-50t	50	270	70	55	230	100	200	60	650	335	430	204
42157912696	VRBG-FIX-100t	100	380	99	77	250	100	240	79	825	392	510	441.96

## Technical data

Method of lift										
Number of legs	1	1	2	2	2	2	2	3/4	3/4	3/4
Angle of inclination $\beta$	0°	90°	0°	90°	0-45°	>45-60°	Un-symm.	0-45°	>45-60°	Un-symm.
Factor	1	1	2	2	1.4	1	1	2.1	1.5	1
WLL stamped in plate	For the max. total load weight >G< in [t]									
VRBG / VRBG-FIX / VRBS 31.5 t	31.5	31.5	63	63	45	31.5	31.5	67	47.5	31.5
VRBG-FIX 50 t	50	50	100	100	70	50	50	105	75	50
VRBG-FIX 100 t	100	100	200	200	140	100	100	210	150	100

# Blueprint

