

Weld-on Lifting Ring RUD VLBS-U with spring

Product information



- Suspension ring pivots 180°
- Suspension ring & weld-on-block of the VLBS-U are undetachable
- Suspension ring can be angled into position (VLBS-U)

Clamping spring works as a noise reduction and holds the suspension ring in the requested position; therefore simple hinge of lashing mean possible.

... [Read more](#)

Marking: According to standard


Temperature range: -40° up to +200°C

Standard: EN 1677-1

Safety factor: 4:1

Weld-on Lifting Ring RUD VLBS-U with spring

Blueprint



Technical data

Part code	Code	WLL ton	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	T mm	Weight kg
42157993035	VLBS-U-1,5t with spring	1.5	33	66	25	38	40	14	33	14	65	0.35
42157994830	VLBS-U-2,5t with spring	2.5	38	77	28	45	47	16	40	16	75	0.53
42157993036	VLBS-U-4t with spring	4	42	87	31	51	52	18	46	16	83	0.72
42157993037	VLBS-U-6,7t with spring	6.7	61	115	44	67	73	24	60	22.5	117	1.89
42157993040	VLBS-U-10t with spring	10	75	129	55	67	71	26.5	60	26.5	126	2.76
42157906640	VLBS-U-16t with spring	16	96	192	70	100	106	40	90	26	176	7.12