

Weld-on Lifting Ring RUD VRBS-FIX



Product information

Load ring for plane surfaces. 180° pivoting. Continuous weld seam reduces likelihood of subsurface corrosion.

- No complex leveling of the components to each other
- No crevice corrosion: endless HY weld seam
- Clamping spring holds all parts together

Material: CrNiMo Steel

Marking: According to standard, CE-marked

Temperature range: -20°C up to 200°C

Finish: Pink powder coated

Standard: EN 1677-1

Safety factor: 4:1

Part code	Code	WLL ton	A,	B,	C,	D,	E,	F,	T mm	Weight kg
42157999019	VRBS-FIX - 4t	4	60	14	39	48	132	69	74	0.94
42157999020	VRBS-FIX - 6.7t	6.7	88	20	50	60	167	91	97	2.24
42157999021	VRBS-FIX - 10t	10	100	22	60	65	191	100	108	3.72
42157999301	VRBS-FIX - 16t	16	130	30	72	90	267	134	140	8.23
42157999302	VRBS-FIX - 31.5t	31.5	160	42	99	130	366	195	202	18.36
42157906272	VRBS-FIX - 50t	50	246	70	148	230	596	335	330	64.7
42157906273	VRBS-FIX - 100t	100	320	97	195	250	763	392	390	148.2

Technical data

RUD Load table VRBS FIX

Blueprint

