

## Lifting Beam PF

### Product information



Specifically designed for lifting suspended loads requiring multiple anchorage points, this fixed lifting beam ensures optimal stability during load transfers. Its robust structure is based on a main beam made of high quality steel, guaranteeing extended service life in industrial environments.

#### Main features:

- Central attachment: Equipped with a fixed upper lifting ring for direct connection to the overhead crane or crane hook.
- Lower lifting points: Two welded lifting eyes at each end, precisely positioned to balance the load.
- Versatility: Each eye is sized to accommodate shackles or shackle/hook assemblies.

**Material:** Steel

**Marking:** CE-marked, TRACTION LEVAGE Logo, model number, WLL, certificate number, year of manufacture, serial number, weight

**Temperature range:** -20° up to +90°C

**Finish:** Painted yellow (This beam can be ordered unpainted)

**Warning:** Do not use this lifting beam for lifting or transporting people!

Part code	WLL ton	Length m	L	E mm	A	B mm	C mm	D mm	F mm	G mm	H mm
6205182612	1	1	1,000	15	100	150	28	14.2	18.1	15	316.9
6205182613	1	2	2,000	15	100	150	28	14.2	18.1	15	316.9
6205182614	1	3	3,000	15	100	150	28	14.2	18.1	15	316.9
6205182615	1	4	4,000	15	100	150	28	14.2	18.1	15	316.9
6205182616	1	5	5,000	15	100	150	28	14.2	18.1	15	316.9
6205182617	1	6	6,000	20	100	150	28	18	22	15	366
6205182618	2	1	1,000	15	100	150	28	14.2	18.1	15	316.9

6205182619	2	2	2,000	15	100	150	28	14.2	18.1	15	316.9
6205182620	2	3	3,000	20	100	150	28	18	22	15	366
6205182621	2	4	4,000	20	100	150	28	18	22	15	366
6205182622	2	5	5,000	20	100	150	28	18	22	15	366
6205182623	2	6	6,000	25	100	165	30	22	27.5	20	429.5
6205182624	3.2	1	1,000	30	120	200	32.5	25	28	25	418
6205182625	3.2	2	2,000	30	120	200	32.5	25	28	25	418
6205182626	3.2	3	3,000	30	120	200	32.5	25	28	25	418
6205182627	3.2	4	4,000	25	100	165	30	22	27.5	20	429.5
6205182628	3.2	5	5,000	25	100	165	30	22	27.5	20	429.5
6205182629	3.2	6	6,000	25	100	165	30	22	27.5	20	429.5
6205182630	4	1	1,000	30	120	200	32.5	25	28	25	418
6205182631	4	2	2,000	30	120	200	32.5	25	28	25	418
6205182632	4	3	3,000	30	120	200	32.5	25	28	25	418
6205182633	4	4	4,000	25	100	165	30	22	27.5	20	429.5
6205182634	4	5	5,000	25	100	165	30	22	27.5	20	429.5
6205182635	4	6	6,000	30	120	200	35	25	28	25	519
6205182636	5	1	1,000	30	120	200	32.5	25	28	25	418
6205182637	5	2	2,000	30	120	200	32.5	25	28	25	418
6205182746	5	3	3,000	30	150	220	45	28	33.5	25	503.5
6205182747	5	4	4,000	30	150	220	45	28	33.5	25	503.5
6205182748	5	5	5,000	25	100	165	30	25	28	25	519
6205182749	5	6	6,000	30	120	200	35	25	28	25	519

6205182638	6.3	1	1,000	30	150	220	45	28	33.5	25	503.5
6205182639	6.3	2	2,000	30	150	220	45	28	33.5	25	503.5
6205182750	6.3	3	3,000	30	150	220	45	28	33.5	25	503.5
6205182751	6.3	4	4,000	30	150	220	50	31	38	30	539
6205182752	6.3	5	5,000	30	150	220	50	31	38	30	539
6205182753	6.3	6	6,000	30	150	220	50	31	38	30	599
6205182640	8	1	1,000	30	150	220	45	28	33.5	25	503.5
6205182641	8	2	2,000	30	150	220	45	28	33.5	25	503.5
6205182780	8	3	3,000	30	150	220	50	31	38	30	539
6205182781	8	4	4,000	30	150	220	50	31	38	30	539
6205182782	8	5	5,000	30	150	220	50	31	38	30	599
6205182783	8	6	6,000	30	150	220	50	31	38	30	599
6205182642	10	1	1,000	30	150	220	50	31	38	30	539
6205182643	10	2	2,000	30	150	220	50	31	38	30	539
6205182784	10	3	3,000	30	150	220	50	31	38	30	599
6205182785	10	4	4,000	30	150	220	50	31	38	30	599
6205182786	10	5	5,000	30	150	220	50	31	38	30	599
6205182787	10	6	6,000	30	150	220	50	31	38	30	599

# Blueprint

