Lifting Solutions Group
Axel Johnson International

Lifting Beam PF

Product information



Specifically designed for lifting suspended loads requiring multiple anchorage points, this fixed lifting beam ensures optimal stability during load transfers. Its robust structure is based on a main beam made of high quality steel, guaranteeing extended service life in industrial environments.

Main features:

- Central attachment: Equipped with a fixed upper lifting ring for direct connection to the overhead crane or crane hook.
- Lower lifting points: Two welded lifting eyes at each end, precisely positioned to balance the load.
- Versatility: Each eye is sized to accommodate shackles or shackle/hook assemblies.

... *Read more*


Material: Steel
Marking: CE-mark, TRACTION LEVAGE Logo, model number, WLL, certificate number, year of manufacture, serial number, weight
Temperature range: -20° up to +90°C
Finish: Painted yellow (This beam can be ordered unpainted)
Warning: Do not use this lifting beam for lifting or transporting people!

Traction Levage
marketingtl@traclev.com
© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Lifting Beam PF

Blueprint



Technical data

Part code	WLL ton	Length m	L mm	E mm	A mm	B mm	C mm	D mm	F mm	G mm	H mm
6205182612	1	1	1,000	15	100	150	28	14.2	18.1	15	316.9
6205182613	1	2	2,000	15	100	150	28	14.2	18.1	15	316.9
6205182614	1	3	3,000	15	100	150	28	14.2	18.1	15	316.9
6205182615	1	4	4,000	15	100	150	28	14.2	18.1	15	316.9
6205182616	1	5	5,000	15	100	150	28	14.2	18.1	15	316.9
6205182617	1	6	6,000	20	100	150	28	18	22	15	366
6205182618	2	1	1,000	15	100	150	28	14.2	18.1	15	316.9
6205182619	2	2	2,000	15	100	150	28	14.2	18.1	15	316.9
6205182620	2	3	3,000	20	100	150	28	18	22	15	366
6205182621	2	4	4,000	20	100	150	28	18	22	15	366
6205182622	2	5	5,000	20	100	150	28	18	22	15	366
6205182623	2	6	6,000	25	100	165	30	22	27.5	20	429.5
6205182624	3.2	1	1,000	30	120	200	32.5	25	28	25	418
6205182625	3.2	2	2,000	30	120	200	32.5	25	28	25	418
6205182626	3.2	3	3,000	30	120	200	32.5	25	28	25	418
6205182627	3.2	4	4,000	25	100	165	30	22	27.5	20	429.5
6205182628	3.2	5	5,000	25	100	165	30	22	27.5	20	429.5
6205182629	3.2	6	6,000	25	100	165	30	22	27.5	20	429.5
6205182630	4	1	1,000	30	120	200	32.5	25	28	25	418
6205182631	4	2	2,000	30	120	200	32.5	25	28	25	418
6205182632	4	3	3,000	30	120	200	32.5	25	28	25	418
6205182633	4	4	4,000	25	100	165	30	22	27.5	20	429.5

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Lifting Beam PF

Technical data

Part code	WLL ton	Length m	L mm	E mm	A mm	B mm	C mm	D mm	F mm	G mm	H mm
6205182634	4	5	5,000	25	100	165	30	22	27.5	20	429.5
6205182635	4	6	6,000	30	120	200	35	25	28	25	519
6205182636	5	1	1,000	30	120	200	32.5	25	28	25	418
6205182637	5	2	2,000	30	120	200	32.5	25	28	25	418
6205182746	5	3	3,000	30	150	220	45	28	33.5	25	503.5
6205182747	5	4	4,000	30	150	220	45	28	33.5	25	503.5
6205182748	5	5	5,000	25	100	165	30	25	28	25	519
6205182749	5	6	6,000	30	120	200	35	25	28	25	519
6205182638	6.3	1	1,000	30	150	220	45	28	33.5	25	503.5
6205182639	6.3	2	2,000	30	150	220	45	28	33.5	25	503.5
6205182750	6.3	3	3,000	30	150	220	45	28	33.5	25	503.5
6205182751	6.3	4	4,000	30	150	220	50	31	38	30	539
6205182752	6.3	5	5,000	30	150	220	50	31	38	30	539
6205182753	6.3	6	6,000	30	150	220	50	31	38	30	599
6205182640	8	1	1,000	30	150	220	45	28	33.5	25	503.5
6205182641	8	2	2,000	30	150	220	45	28	33.5	25	503.5
6205182780	8	3	3,000	30	150	220	50	31	38	30	539
6205182781	8	4	4,000	30	150	220	50	31	38	30	539
6205182782	8	5	5,000	30	150	220	50	31	38	30	599
6205182783	8	6	6,000	30	150	220	50	31	38	30	599
6205182642	10	1	1,000	30	150	220	50	31	38	30	539
6205182643	10	2	2,000	30	150	220	50	31	38	30	539
6205182784	10	3	3,000	30	150	220	50	31	38	30	599
6205182785	10	4	4,000	30	150	220	50	31	38	30	599
6205182786	10	5	5,000	30	150	220	50	31	38	30	599
6205182787	10	6	6,000	30	150	220	50	31	38	30	599

© November 2026 - All Rights Reserved