

## Double Swivel Lifting Ring Codipro FE.DSS UP-Female

### Product information



The FE DSS lifting shackle is specially designed for simultaneously lifting and rotating loads. Its double swivel action ensures perfect line up with the lifting sling. The ring can swivel under the load. The ring swivels 180° and has a rotating range of 360°.

#### Features:

- Swiveling under load
- Usable for any kind of lifting operation
- The tightening torque is stamped on all lifting rings in the GRADUP range ... [Read more](#)

**Material:** High tensile steel

**Marking:** According to standard, CE-marked

**Temperature range:** -20°C up to +200°C


**Standard:** EN 1677-1

*except grade/WLL*

**Safety factor:** 5:1

## Double Swivel Lifting Ring Codipro FE.DSS UP-Female

### Blueprint



### Technical data

Part code	WLL ton	Thread	Torque Nm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	L Maxi mm	S mm	Weight kg
4215FEDSSM24UP	4.5	M 24 (x3)	160	66	31	70	98	73	149	33	66	50	5.1
4215FEDSSM27UP	5.2	M 27 (x3)	200	66	31	70	98	73	149	33	66	50	5.1
4215FEDSSM30UP	7.5	M 30 (x3.5)	250	66	31	70	98	73	149	33	66	50	5.1
4215FEDSSM33UP	8	M 33 (x3.5)	250	66	31	70	98	73	149	33	66	50	5.1
4215FEDSSM36UP	10	M 36 (x4)	320	66	31	70	98	73	149	33	66	50	5.1
4215FEDSSM39UP	12	M 39 (x4)	320	89	38	95	123	91	182	45	89	60	10
4215FEDSSM42UP	13	M 42 (x4,5)	400	89	38	95	123	91	182	45	89	60	10
4215FEDSSM45UP	14.5	M 45 (x4,5)	400	89	38	95	123	91	182	45	89	60	10
4215FEDSSM48UP	17	M 48 (x5)	600	89	38	95	123	91	182	45	89	60	10
4215FEDSSM52UP	19	M 52 (x5)	600	89	38	95	123	91	182	45	89	60	10