Lifting Solutions Group
Axel Johnson International

RSB System

Product information



The RSB system consists of a pulley, a wire mesh sling, a tie and a hook. It offers a safety factor of 4. Unlike other products, the mesh sling is made of riveted chain links and not welded, thus avoiding the need to replace the entire sling when damaged.

The RBS system is very flexible and adapts perfectly to different forms of load. This system is robust and slash-resistant. Ideal for handling coils, it eliminates tipping issues and does not damage coils. A protective PVC sheath may be added on request.

The RSB system comes with an EC declaration and is readily available. It has legible marking and an individual traceability code.

Machinery Directive 2006/42/CE

... *Read more*

Marking: CE-mark
Temperature range: -20°C +100°C

Safety factor: 4:1

Traction Levage
marketingtl@traclev.com

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

RSB System

Blueprint



Technical data

Part code	EWL m	WLL ton	A mm	B mm	L mm	LD mm	Weight kg
3901441C	1.5	3	110	80	1,500	2,500	14
3901441D	1.8	6	150	100	1,800	3,000	30
3901441E	2.15	10	177	135	2,150	3,500	45
3901441F	2.5	15	300	200	2,500	4,000	125
3901441G	2.75	20	300	200	2,750	4,500	150

© November 2026 - All Rights Reserved