

Chain Sling Powertex 1-leg with Masterlink MC1 and Latch Hook, Grade 10

Product information



The Chain Sling Powertex 1-leg MC-1 with latch hook is a single-leg lifting assembly for general industrial use. It features an MC-1 master link with an integrated shortening function, reducing loose components and creating a more compact and manageable lifting setup.

It is designed for controlled vertical lifting where fast connection, quick length adjustment, and predictable performance are required.

The assembly includes the MC-1 master link, a Grade 10 chain, a latch hook, and a marking plate with WLL information, providing a complete, ready-to-use configuration.

Best used for:

- Straight vertical lifts with a single lifting point
- Applications where a compact setup with integrated shortening is preferred
- Repetitive lifting where fast and efficient hook connection improves handling speed

Product benefits

- MC-1 master link integrates the shortening function, reducing loose components and simplifying assembly configuration
- Integrated shortening allows quick length adjustment without adding separate shortening hooks
- Compact design supports a clearer overview during use and inspection, helping reduce handling errors
- Latch hook enables fast and secure attachment, reducing connection time during repetitive lifting operations
- Grade 10 chain provides higher capacity compared to Grade 8, enabling compact setups without increasing chain diameter

... [Read more](#)

Material: Alloy steel

Marking: According to standard, CE-marked

Temperature range: -40°C up to +200°C without reduction in WLL

Finish: Red powder paint

Standard: EN 818-4

(+25 % WLL)

Safety factor: 4:1

Grade: 10

Chain Sling Powertex 1-leg with Masterlink MC1 and Latch Hook, Grade 10

Technical data

Part code	EWL m	Chain diameter mm	WLL ton
240500600100280	1	6	1.4
240500600200280	2	6	1.4
240500600300280	3	6	1.4
240500600400280	4	6	1.4
240500600500280	5	6	1.4
240500600600280	6	6	1.4
240500600700280	7	6	1.4
240500600800280	8	6	1.4
240500800100280	1	8	2.5
240500800200280	2	8	2.5
240500800300280	3	8	2.5
240500800400280	4	8	2.5
240500800500280	5	8	2.5
240500800600280	6	8	2.5
240500800700280	7	8	2.5
240500800800280	8	8	2.5
240501000100280	1	10	4
240501000200280	2	10	4
240501000300280	3	10	4
240501000400280	4	10	4
240501000500280	5	10	4
240501000600280	6	10	4
240501000700280	7	10	4
240501000800280	8	10	4
240501300100280	1	13	6.7
240501300200280	2	13	6.7
240501300300280	3	13	6.7
240501300400280	4	13	6.7
240501300500280	5	13	6.7
240501300600280	6	13	6.7

Chain Sling Powertex 1-leg with Masterlink MC1 and Latch Hook, Grade 10

Technical data

Part code	EWL m	Chain diameter mm	WLL ton
240501300700280	7	13	6.7
240501300800280	8	13	6.7
240501600100280	1	16	10
240501600200280	2	16	10
240501600300280	3	16	10
240501600400280	4	16	10
240501600500280	5	16	10
240501600600280	6	16	10
240501600700280	7	16	10
240501600800280	8	16	10