

## Chain Sling Powertex 2-leg with Masterlink MC2 and Latch Hooks, Grade 10

### Product information



The Chain Sling Powertex 2-leg MC-2 with latch hooks is a two-leg lifting assembly for general industrial use. It features an MC-2 master link with an integrated shortening function, reducing the number of components and creating a more compact and manageable lifting setup.

It is designed for controlled lifting where fast connection, quick length adjustment, and predictable performance are required.

The assembly includes the MC-2 master link, Grade 10 chain, latch hooks, and a marking plate with WLL information, providing a complete, ready-to-use configuration.

#### When to choose this product:

##### Best for:

- Balanced lifting using two lifting points
- Applications where a compact setup with integrated shortening is preferred
- Repetitive lifting where fast and efficient hook connection improves handling speed

#### Product benefits

- MC-2 master link integrates shortening functions on both legs, reducing the number of components and simplifying assembly configuration
- Individual leg shortening allows quick length adjustment without adding separate shortening hooks
- Compact design supports a clearer overview during use and inspection, helping reduce handling errors
- Latch hook enables fast and secure attachment, reducing connection time during repetitive lifting operations
- Grade 10 chain provides higher capacity compared to Grade 8 chains ... [Read more](#)

**Material:** Alloy steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40°C up to +200°C without reduction in WLL

**Finish:** Red powder paint

**Standard:** EN 818-4

(+25 % WLL)

**Safety factor:** 4:1

**Grade:** 10

# Chain Sling Powertex 2-leg with Masterlink MC2 and Latch Hooks, Grade 10

## Technical data

Part code	EWL m	Chain diameter mm	WLL ton	WLL 0-45° t	WLL 45-60° t
240800600100230	1	6	2	2	1.4
240800600200230	2	6	2	2	1.4
240800600300230	3	6	2	2	1.4
240800600400230	4	6	2	2	1.4
240800600500230	5	6	2	2	1.4
240800600600230	6	6	2	2	1.4
240800600700230	7	6	2	2	1.4
240800600800230	8	6	2	2	1.4
240800800100230	1	8	3.55	3.55	2.5
240800800200230	2	8	3.55	3.55	2.5
240800800300230	3	8	3.55	3.55	2.5
240800800400230	4	8	3.55	3.55	2.5
240800800500230	5	8	3.55	3.55	2.5
240800800600230	6	8	3.55	3.55	2.5
240800800700230	7	8	3.55	3.55	2.5
240800800800230	8	8	3.55	3.55	2.5
240801000100230	1	10	5.6	5.6	4
240801000200230	2	10	5.6	5.6	4
240801000300230	3	10	5.6	5.6	4
240801000400230	4	10	5.6	5.6	4
240801000500230	5	10	5.6	5.6	4
240801000600230	6	10	5.6	5.6	4
240801000700230	7	10	5.6	5.6	4
240801000800230	8	10	5.6	5.6	4
240801300100230	1	13	9.5	9.5	6.7
240801300200230	2	13	9.5	9.5	6.7
240801300300230	3	13	9.5	9.5	6.7
240801300400230	4	13	9.5	9.5	6.7
240801300500230	5	13	9.5	9.5	6.7
240801300600230	6	13	9.5	9.5	6.7

## Chain Sling Powertex 2-leg with Masterlink MC2 and Latch Hooks, Grade 10

### Technical data

Part code	EWL m	Chain diameter mm	WLL ton	WLL 0-45° t	WLL 45-60° t
240801300700230	7	13	9.5	9.5	6.7
240801300800230	8	13	9.5	9.5	6.7
240801600200230	2	16	14	14	10
240801600300230	3	16	14	14	10
240801600400230	4	16	14	14	10
240801600500230	5	16	14	14	10
240801600600230	6	16	14	14	10
240801600700230	7	16	14	14	10
240801600800230	8	16	14	14	10