

Chain Sling Powertex 2-leg with Masterlink MC2 and Safety Hooks, Grade 10

Product information



The Chain Sling Powertex 2-leg MC2 with safety hooks is a two-leg lifting assembly for general industrial use. It features an MC2 master link with integrated shortening functions on both legs, reducing the number of components and creating a more compact and manageable lifting setup.

It is designed for balanced lifting where load distribution, individual leg adjustment, and predictable performance are required.

The assembly includes the MC-2 Master Link, Grade 10 chain, safety hooks, and a marking plate with WLL information, providing a complete, ready-to-use configuration.

When to choose this product

Best for:

- Balanced lifting using two lifting points
- Applications where a compact setup with integrated shortening is preferred
- Lifting applications where secure hook closure is required to reduce the risk of unintentional release

Product Benefits

- MC-2 master link integrates the shortening function, reducing the number of components and simplifying assembly configuration
- Individual leg shortening allows accurate load balancing without adding separate shortening hooks
- Compact design supports a clearer overview during use and inspection, helping reduce handling errors
- Safety hooks provide secure closure, helping reduce the chance of unintentional hook release during lifting
- Grade 10 chain provides higher capacity compared to Grade 8 chains ... [Read more](#)

Material: Alloy steel

Marking: According to standard, CE-marked

Temperature range: -40°C up to +200°C without reduction in WLL

Finish: Red powder paint

Standard: EN 818-4

(+25 % WLL)

Safety factor: 4:1

Grade: 10

Chain Sling Powertex 2-leg with Masterlink MC2 and Safety Hooks, Grade 10

Technical data

Part code	EWL m	Chain diameter mm	WLL ton	WLL 0-45° t	WLL 45-60° t
240800600100250	1	6	2	2	1.4
240800600200250	2	6	2	2	1.4
240800600300250	3	6	2	2	1.4
240800600400250	4	6	2	2	1.4
240800600500250	5	6	2	2	1.4
240800600600250	6	6	2	2	1.4
240800600700250	7	6	2	2	1.4
240800600800250	8	6	2	2	1.4
240800800100250	1	8	3.55	3.55	2.5
240800800200250	2	8	3.55	3.55	2.5
240800800300250	3	8	3.55	3.55	2.5
240800800400250	4	8	3.55	3.55	2.5
240800800500250	5	8	3.55	3.55	2.5
240800800600250	6	8	3.55	3.55	2.5
240800800700250	7	8	3.55	3.55	2.5
240800800800250	8	8	3.55	3.55	2.5
240801000100250	1	10	5.6	5.6	4
240801000200250	2	10	5.6	5.6	4
240801000300250	3	10	5.6	5.6	4
240801000400250	4	10	5.6	5.6	4
240801000500250	5	10	5.6	5.6	4
240801000600250	6	10	5.6	5.6	4
240801000700250	7	10	5.6	5.6	4
240801000800250	8	10	5.6	5.6	4
240801300100250	1	13	9.5	9.5	6.7
240801300200250	2	13	9.5	9.5	6.7
240801300300250	3	13	9.5	9.5	6.7
240801300400250	4	13	9.5	9.5	6.7
240801300500250	5	13	9.5	9.5	6.7
240801300600250	6	13	9.5	9.5	6.7

Chain Sling Powertex 2-leg with Masterlink MC2 and Safety Hooks, Grade 10

Technical data

Part code	EWL m	Chain diameter mm	WLL ton	WLL 0-45° t	WLL 45-60° t
240801300700250	7	13	9.5	9.5	6.7
240801300800250	8	13	9.5	9.5	6.7
240801600200250	2	16	14	14	10
240801600300250	3	16	14	14	10
240801600400250	4	16	14	14	10
240801600500250	5	16	14	14	10
240801600600250	6	16	14	14	10
240801600700250	7	16	14	14	10
240801600800250	8	16	14	14	10