

## Chain Sling Powertex 4-leg with Masterlink MC4 and Latch Hooks, Grade 10

### Product information



The Chain Sling Powertex 4-leg MC-4 with latch hooks is a four-leg lifting assembly for general industrial use. It features an MC-4 master link with an integrated shortening function, reducing the number of components and creating a more compact, manageable lifting setup.

It is designed for controlled lifting where fast connection, quick length adjustment, and predictable performance are required.

The assembly includes the MC-4 master link, Grade 10 chain, latch hooks, and a marking plate with WLL information, providing a complete, ready-to-use configuration.

#### When to choose this product:

##### Best for:

- Lifting loads requiring multiple lifting points for stability
- Applications where a compact setup with integrated shortening is preferred
- Repetitive lifting where fast and efficient hook connection improves handling speed

##### Product benefits

- MC-4 master link integrates shortening functions on all legs, reducing the number of components and simplifying assembly configuration
- Integrated shortening allows quick length adjustment without adding separate shortening hooks
- Compact design supports a clearer overview during use and inspection, helping reduce handling errors
- Latch hook enables fast and secure attachment, reducing connection time during repetitive lifting operations
- Grade 10 chain provides higher capacity compared to Grade 8 chains ... [Read more](#)

**Material:** Alloy steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40°C up to +200°C without reduction in WLL

**Finish:** Red powder paint

**Standard:** EN 818-4

(+25 % WLL)

**Safety factor:** 4:1

**Grade:** 10

## Chain Sling Powertex 4-leg with Masterlink MC4 and Latch Hooks, Grade 10

### Technical data

Part code	EWL m	Chain diameter mm	WLL ton	WLL 0-45° t	WLL 45-60° t
241300600100290	1	6	3	3	2.12
241300600200290	2	6	3	3	2.12
241300600300290	3	6	3	3	2.12
241300600400290	4	6	3	3	2.12
241300600500290	5	6	3	3	2.12
241300600600290	6	6	3	3	2.12
241300600700290	7	6	3	3	2.12
241300600800290	8	6	3	3	2.12
241300800100290	1	8	5.3	5.3	3.75
241300800200290	2	8	5.3	5.3	3.75
241300800300290	3	8	5.3	5.3	3.75
241300800400290	4	8	5.3	5.3	3.75
241300800500290	5	8	5.3	5.3	3.75
241300800600290	6	8	5.3	5.3	3.75
241300800700290	7	8	5.3	5.3	3.75
241300800800290	8	8	5.3	5.3	3.75
241301000100290	1	10	8.4	8.4	6
241301000200290	2	10	8.4	8.4	6
241301000300290	3	10	8.4	8.4	6
241301000400290	4	10	8.4	8.4	6
241301000500290	5	10	8.4	8.4	6
241301000600290	6	10	8.4	8.4	6
241301000700290	7	10	8.4	8.4	6
241301000800290	8	10	8.4	8.4	6
241301300200290	2	13	14	14	10
241301300300290	3	13	14	14	10
241301300400290	4	13	14	14	10
241301300500290	5	13	14	14	10
241301300600290	6	13	14	14	10
241301300700290	7	13	14	14	10

## Chain Sling Powertex 4-leg with Masterlink MC4 and Latch Hooks, Grade 10

### Technical data

Part code	EWL m	Chain diameter mm	WLL ton	WLL 0-45° t	WLL 45-60° t
241301300800290	8	13	14	14	10
241301600200290	2	16	21.2	21.2	15
241301600300290	3	16	21.2	21.2	15
241301600400290	4	16	21.2	21.2	15
241301600500290	5	16	21.2	21.2	15
241301600600290	6	16	21.2	21.2	15
241301600700290	7	16	21.2	21.2	15
241301600800290	8	16	21.2	21.2	15