Lifting Solutions Group
Axel Johnson International

Chain Sling Powertex 4-leg with Masterlink MC4 and Safety Hooks, Grade 10

Product information

The Chain Sling Powertex 4-leg MC-4 with safety hooks is a four-leg lifting assembly for general industrial use. It features an MC-4 master link with integrated shortening functions on all 4 legs, reducing the number of components and creating a more compact and manageable lifting setup.

It is designed for balanced lifting where load distribution, individual leg adjustment, and predictable performance are required.

The assembly includes the MC-4 Master Link, Grade 10 chain, safety hooks, and a marking plate with WLL information, providing a complete, ready-to-use configuration.

Best used for:

- Lifting loads requiring multiple lifting points for stability
- Applications where a compact setup with integrated shortening is preferred
- Lifting applications where secure hook closure is required to reduce the risk of unintentional release

Product Benefits

- MC-4 master link integrates the shortening function, reducing the number of components and simplifying assembly configuration
- Individual leg shortening allows accurate load balancing without adding separate shortening hooks
- Compact design supports a clearer overview during use and inspection, helping reduce handling errors
- Safety hooks provide secure closure, helping reduce the chance of unintentional hook release during lifting
- Grade 10 chain provides higher capacity compared to Grade 8, enabling compact setups without increasing chain diameter

... *Read more*

Material: Alloy steel
Marking: According to standard, CE-marked
Temperature range: -40°C up to +200°C without reduction in WLL
Finish: Red powder paint
Standard: EN 818-4, AS 3776
(+25 % WLL)

Safety factor: 4:1
Grade: 10

Traction Levage
marketingtl@traclev.com

© October 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Chain Sling Powertex 4-leg with Masterlink MC4 and Safety Hooks, Grade 10

Technical data

Part code	EWL m	Chain diameter mm	WLL ton	WLL 0-45° t	WLL 45-60° t
241300600100310	1	6	3	3	2.12
241300600200310	2	6	3	3	2.12
241300600300310	3	6	3	3	2.12
241300600400310	4	6	3	3	2.12
241300600500310	5	6	3	3	2.12
241300600600310	6	6	3	3	2.12
241300600700310	7	6	3	3	2.12
241300600800310	8	6	3	3	2.12
241300800100310	1	8	5.3	5.3	3.75
241300800200310	2	8	5.3	5.3	3.75
241300800300310	3	8	5.3	5.3	3.75
241300800400310	4	8	5.3	5.3	3.75
241300800500310	5	8	5.3	5.3	3.75
241300800600310	6	8	5.3	5.3	3.75
241300800700310	7	8	5.3	5.3	3.75
241300800800310	8	8	5.3	5.3	3.75
241301000100310	1	10	8.4	8.4	6
241301000200310	2	10	8.4	8.4	6
241301000300310	3	10	8.4	8.4	6
241301000400310	4	10	8.4	8.4	6
241301000500310	5	10	8.4	8.4	6
241301000600310	6	10	8.4	8.4	6
241301000700310	7	10	8.4	8.4	6
241301000800310	8	10	8.4	8.4	6
241301300200310	2	13	14	14	10
241301300300310	3	13	14	14	10
241301300400310	4	13	14	14	10
241301300500310	5	13	14	14	10
241301300600310	6	13	14	14	10
241301300700310	7	13	14	14	10

© October 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Chain Sling Powertex 4-leg with Masterlink MC4 and Safety Hooks, Grade 10

Technical data

Part code	EWL m	Chain diameter mm	WLL ton	WLL 0-45° t	WLL 45-60° t
241301300800310	8	13	14	14	10
241301600200310	2	16	21.2	21.2	15
241301600300310	3	16	21.2	21.2	15
241301600400310	4	16	21.2	21.2	15
241301600500310	5	16	21.2	21.2	15
241301600600310	6	16	21.2	21.2	15
241301600700310	7	16	21.2	21.2	15
241301600800310	8	16	21.2	21.2	15

© October 2026 - All Rights Reserved